



Features:

EUROLITE LED IP PAR 3x12W HCL

Compact, weather-proof DMX spot (IP65) with 3 x 12 W 6in1 LED (RGBWA+UV)

- Equipped with 3 high-power 12 W 6in1 LEDs in the colors red, green, blue, amber, white and UV
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Power terminals for power linking up to 8 units
- 3 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via DMX
- Flicker-free
- With a beam angle of 20°

Logistic

- Suitable for outdoor use IP65

ROADINGER Flightcase 4x LED IP PAR 3x12W HCL

Trunk case, PRO version

- For optimal security
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	18.28 kg
---------	----------

EUROLITE LED IP PAR 3x12W HCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	3 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 5; 6; 9; 12; 7
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	DMX
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	40°
Housing color:	Black
Dimensions:	Width: 18.1 cm Depth: 10.2 cm Height: 20.6 cm
Weight:	2.57 kg

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP PAR 3x12W HCL

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	20.5 cm x 16.5 cm x 10 cm
Accessory compartment:	10.5 cm x 37 cm x 10 cm
Inside dimensions:	59 cm x 39 cm x 12 cm
Dimensions:	Width: 60 cm Depth: 40 cm Height: 22 cm
Weight:	8.00 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 2 x adapter cable