

EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + SB-4 Soft Bag L

Battery-powered LED uplight with QuickDMX wireless receiver

Art. No.: 20000389

GTIN:



List price: 1426.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 9,5h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
- Flicker-free
- With a beam angle of 22°
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Mains input and output for power linking up to 8 units
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Cordless, flexible and versatile
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With Dividers
- With 2 Outside pockets
- With 4 Device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight:	14,88 kg
---------	----------

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Battery pack:	Battery operation up to 9,5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
Preprogrammed in:	Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	22°
Beam angle (1/2 peak):	22°

Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16,7 cm Depth: 13,8 cm Height: 18,8 cm
Weight:	3,59 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	520 g