

OMNITRONIC Set CMX-2000 + 2x DD-5220L

Set with digital DJ mixer/controller and two turntables

Art. No.: 2000395

GTIN:



The article is no longer in our assortment.

Features:

OMNITRONIC CMX-2000 2+1-channel MIDI controller

Digital DJ mixer and controller incl. Virtual DJ 7 LE

- 2-channel DJ mixer/MIDI controller bundled with Virtual DJ
- Optimized layout for Virtual DJ and Traktor PRO 2 - Virtual DJ 7 LE voucher included
- Traktor PRO 2 and Serato Scratch Live mappings available with full support for scratch and sample decks
- Flexibly combines stand-alone mixing of analog sources with MIDI control for DJ software
- Built-in DVS audio system for direct use of timecode systems with vinyl or CD in Virtual DJ and other open applications via USB
- 2 input channels with routing facility for analog inputs and MIDI decks as desired
- Full-fledged MIDI sections with 2 layers for 4-deck control
- Perfect MIDI control for file browsing, transportation, hot cues, samples, sample recorder, loops, effects, pitch und video transitions
- Advanced setup options for scratch DJs: crossfader and channel faders with adjustable curve and reverse selectors
- Built-in USB sound card 4 IN/4 OUT
- Supports Mac OSX, Windows XP, Vista, 7
- Professional-grade metal chassis with replaceable crossfader (45 mm)
- 2 line and 2 line/phono RCA inputs for connecting CD players, turntables and other external hardware
- 2 AUX inputs (3.5 mm/6.3 mm jack) connect MP3 players and tablets
- Mic input (XLR/6.3 mm jack) with tone control and talkover
- 2 master outputs (XLR/RCA) for PA applications
- Booth output (RCA), independently adjustable
- 3.5 mm/6.3 mm jack dual headphones output with cue mix control

Logistic

- Bright color-coded LED buttons provide optimal visual feedback while triggering loops, samples, effects and cue points
- User-definable LED modes for Serato Scratch Live
- Dual-function audio/video crossfader for video performances within Virtual DJ
- 3-band EQ (high, mid, low) and HP/LP filter per channel
- Mixer section switchable between analog mode and MIDI mode
- File selector encoder and 2 load buttons for mouseless music library control
- 8 Hot Cue buttons per channel
- Auto Loop function with Beat Jump (Loop Cut), manual Loop In/Out buttons
- FX/sampler units with 4 parameter controls and 4 buttons per channel
- Various controls for GUI, mixer and video
- Shift button for various dual-button operations
- Separate VU meters for master and PFL signal
- Crossfader with faderstart function for compatible CD players
- Compatible to any MIDI-controlled DJ software including Serato Scratch Live, Traktor, Ableton Live
- All MIDI control elements can be edited and freely assigned
- ASIO drivers with minimum latency and high-quality audio characteristics available for download (PC)
- The device can be connected via USB to the PC in connection with Virtual DJ
Midi capable

OMNITRONIC DD-5220L Turntable bk

Direct drive DJ turntable "Ultra Torque" with switchable phono/line output

- Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Pitch range: $\pm 10\%$, $\pm 20\%$, $\pm 50\%$

Package contents

- 1 x device, 1 x power cord, 1 x turntable platter, 1 x felt mat, 1 x shellset, 1 x balance weights, 1 x plug (male), 1 x adapter, 1 x rCA cable, 1 x user manual

Technical specifications:

Weight: 26,50 kg

OMNITRONIC CMX-2000 2+1-channel MIDI controller

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 14 W

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

USB port: USB 2.0, Typ B

PC connect:	Virtual DJ via USB Midi capable
Dimensions:	Width: 36 cm Depth: 26,5 cm Height: 10,5 cm
Weight:	3,90 kg
Inputs:	
Line:	2 x stereo RCA
Line/phono:	2 x stereo RCA, switchable
DJ microphone:	combination XLR/6.3 mm jack, bal.
Aux:	3.5 mm jack and stereo RCA
Outputs:	
Master:	XLR L/R and stereo RCA
Booth:	stereo RCA
Headphones output:	3.5 mm and 6.3 mm jack
Converter:	16 bits
Sample rate:	48 kHz
Faderstart:	2 x 3.5 mm jack

OMNITRONIC DD-5220L Turntable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	15,00 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with Euro plug
Frequency range:	20 - 20000 Hz
Drive type:	Quarz-controlled direct drive Brushless DC motor
Drive:	Initial torque: 4,5 kg/cm Start time: 0.2 - 6 sec, adjustable Stop time: 0.2 - 6 sec, adjustable Speed change time: <1s 1khz 5cm/sec
Wow and flutter:	<0,1 % WRMS
Rumble:	60 dB DIN B
Speed:	33 RPM; 45 RPM; 78 RPM forward/backward
Tone arm:	S-shape with Cardan"s suspension Length: 230 Tonearm heigh: 8 - 10.5 mm adjustable Overhang: 15 mm Stylus pressure: 0-4 g, adjustable
Output level:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Connections:	Output: line/phono via 1 x stereo RCA
Pitch range:	±10%, ±20%, ±50%
Dimensions:	Width: 45 cm Depth: 35,3 cm Height: 15,6 cm

Weight:	11,30 kg
<hr/>	
Turntable platter	
<hr/>	
Material:	Metal
<hr/>	
Dimensions:	Diameter: Ø 33,2 cm
<hr/>	
Weight:	1,425 kg
<hr/>	