

## EUROLITE Set 4x AKKU TL-3 TCL QuickDMX + Case with charging function Art. No.: 20000399

4x Spot for lighting within trussing, 3 x 3 W 3in1 LED including PRO Flightcase charging function GTIN:



**List price: 1069.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
- Flicker-free
- With a beam angle of 11°
- LCD display
- For application areas such as: Wedding/gala/events; mobile use; Stage; mobile djs / entertainer
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- 3 rubber feet
- Silent operation
- Application possibility: Standing; suspended

#### Package contents

### Logistic

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity

### ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

#### Trunk case

- With 4 Device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x device, 1 x power cord, 1 x user manual

### Technical specifications:

---

Weight: 13,58 kg

---

### EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, F 5 A
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone

Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	24°
Housing color:	Black
Attachment system:	M10 thread
Display type:	LCD display
Transport aid:	3 x rubber feet
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 14,5 cm
Weight:	1,27 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A Fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Compartment dimensions:	15,5 cm x 15,5 cm x 11,5 cm
Accessory compartment:	9 cm x 34 cm x 11,5 cm
Dimensions:	Width: 57 cm Depth: 37 cm Height: 24,5 cm
Weight:	8,50 kg