

EUROLITE Set 4x LED BAR-12 QCL RGBA + 2x Soft Bag + Controller

Art. No.: 20000403

GTIN:



The article is no longer in our assortment.

Features: Logistic

EUROLITE LED BAR-12 QCL RGBA Bar

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBA LED

- 12 powerful LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Silent operation
- Application possibility: Suspended; wall mounting

Package contents

1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile, black
- Interior with foam padding
- 2 carrying straps
- 1 x shoulder strap

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Can transmit up to 8 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing

Technical specifications:

Weight: 13,92 kg

EUROLITE LED BAR-12 QCL RGBA Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling

Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 110 cm Depth: 6,5 cm Height: 10 cm
Weight:	2,90 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø10mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	H05VV-F
Cable length:	Approx. 1,2 m
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-12 Soft Bag

20 kg
2 pc/pcs
1 x shoulder strap
Textile
Black
Width: 107 cm
Depth: 17 cm
Height: 18 cm
0,60 kg

EUROLITE DMX LED Operator 2 controller

Pin configuration:	Inside + / outside -
Power consumption:	4,00 W

IP classification:	IP20
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 8
Control:	DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 26,5 cm
	Depth: 16,5 cm
	Height: 5,5 cm
Weight:	1,12 kg
Power supply:	230 V AC, 50 Hz,
	via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector