

EUROLITE Set 2x LED BAR-12 QCL RGBW + Soft Bag

2x Spotlight bar with 12 x 4 W 4in1 LED including soft bag

Art. No.: 20000406

GTIN:



List price: 327.25 €

incl. 19% VAT.

Features:

EUROLITE LED BAR-12 QCL RGBW Bar

LED bar (110 cm) with 12 x 4 watt 4in1 LED (RGBW)

- Operable in stand-alone mode or via DMX
- Microphone sensitivity adjustable via Control Board
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Comfortable addressing and setting via control board with LED display and four operating buttons
- Functions: Static colors, RGBW color blend, color temperature settings, internal programs, dimmer and strobe settings, Master/Slave
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- LED: 12 x high-power 4 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 2; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection
- Controlling by Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional)
- Is in EUROLITE LED PC-Control 512 software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE already preprogrammed
- Flicker-free projection
- Effect: Strobe effect

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

Logistic

- Ideal for 1 or 2 LED bars with 1 meter length
- Large interior with removable divider
- Interior upholstery helps securing and safeguarding the fixtures during transportation
- Made of easy-care nylon
- Handle and shoulder strap

Technical specifications:

Weight: 6,35 kg

EUROLITE LED BAR-12 QCL RGBW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
Power connection:	Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	12 x high-power 4 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); EUROLITE LED PC-Control 512 software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Display type:	4 digits 7-segment LED display
Dimensions:	Length: 1,085 m Depth: 6,5 cm Height: 10 cm
Weight:	2,85 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting

EUROLITE SB-12 Soft Bag

Maximum load:	20 kg
Material:	Textile
Color:	Black
Dimensions:	Width: 1,07 m Depth: 17 cm Height: 18 cm
Weight:	650 g