

EUROLITE Set 4x LED PAR-56 QCL bk + Case + Controller

4x PAR-56 Spot with 9 x 8 W 4in1 LED including flightcase and compact DMX controller

Art. No.: 20000413

GTIN:



List price: 891.31 €

incl. 19% VAT.

Features:

EUROLITE LED PAR-56 QCL Short bk

PAR-56 spot with 9 x 8 W 4in1 LED and RGBW color mixing

- 9 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- For application areas such as: Clubs/dancing school; party room; stage; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE DMX LED EASY Operator 4x4

Compact DMX controller for 4 LED spotlights with up to 4 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBW LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, white and master
- Various modes for the DMX channel sequence selectable
- Manual control via 4 faders
- 1 fader for direct RGBW mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases
- Can transmit up to 20 DMX channels
- Control via DMX; sound to light via microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer
- Silent operation

Package contents

- 1 x controller, 1 x external mains adapter, 1 x user manual

Technical specifications:

Weight:	15,41 kg
---------	----------

EUROLITE LED PAR-56 QCL Short bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief

Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20,5 cm Depth: 17,5 cm Height: 23 cm
Weight:	1,65 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	22 cm x 22 cm x 24 cm
Inside dimensions:	44 cm x 44 cm x 24 cm
Dimensions:	Width: 48,5 cm Depth: 48,5 cm Height: 31 cm
Weight:	7,95 kg

EUROLITE DMX LED EASY Operator 4x4

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases

DMX channels:	Output 20
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 20 cm Depth: 11,5 cm Height: 5,5 cm
Weight:	0,86 kg
Noise classification:	Class 0 (no noise at all)