

EUROLITE Set 2x LED BAR-12 QCL RGBA + Soft Bag

2x Spotlight bar with 12 x 4 W 4in1 LED including soft bag

Art. No.: 20000415

GTIN: 4026397621204



Features:

- 12 LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light´J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>EUROLITE SB-12 Soft Bag
- <h2 class="featureSatz">Practical black soft bag for LED bars (1 m length), adjustable divider</h2>Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps

Logistic

EAN / GTIN: 4026397621204

Weight: 9,50 kg

Length: 1.20 m

Width: 0.30 m

Height: 0.41 m

Bulky product

- 1 x shoulder strap

Technical specifications:

Weight: 8.40 kg

EUROLITE LED BAR-12 QCL RGBA Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 110 cm Depth: 6.5 cm Height: 10 cm
Weight:	2.90 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø20mm; 1 x Ø10mm; 1 x Ø8mm; 2 x Ø7mm

Material:	Metal, 2 mm
Cable construction:	H05VV-F
Cable length:	Approx. 1.2 m
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-12 Soft Bag

Maximum load:	20 kg
Carrying strap:	2 pc/pcs
Transport aid:	1 x shoulder strap
Material:	Textile
Color:	Black
Dimensions:	Width: 107 cm Depth: 17 cm Height: 18 cm
Weight:	0.60 kg

Scope of delivery:

- 1 x light effect
- 2 x mounting bracket
- 1 x power cord
- 2 x knurled screw
- 2 x washer
- 1 x user manual