

OMNITRONIC Set CNP-1 + 2x C-50A black

Art. No.: 20000416

GTIN:



The article is no longer in our assortment.

Features:

OMNITRONIC CNP-1 WLAN Multi-Room Streaming System

Wireless multi-room streaming adapter

- Stream music wirelessly from your smartphone, tablet, PC and Mac
- Multi-room function for synchronous playback in every room
- Intuitive control via app available for iOS and Android
- WLAN standard IEEE 802.11g/b/n
- Supports high-resolution audio files up to 192 kHz and 24 bit
- Supports Apple AirPlay and DLNA/UPnP
- Streams internet radio services
- USB port for hard disks
- Digital optical output (S/PDIF)
- Analog 3.5 mm jack output
- Incl. 3.5 mm to RCA cable and USB power adapter
- Learn more: www.omnitronic.de
- Control via Wi-Fi
- 2.4 GHz license-free worldwide

Logistic

OMNITRONIC C-50A active black 2x

Active 2-way speaker pair with mount, 5" woofers and 50 W RMS

- Dedicated PA speaker system for fixed installations
- 2-way system with 13 cm woofer (5") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- Trapezoidal cabinet for corner installation

- With mounting bracket
- Black metal grille
- Scratchproof and shockproof
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

- 2 x compact cabinet speaker, 1 x user manual, 2 x power cord, 8 x screw, 8 x washer

Technical specifications:

Weight:	12,81 kg
---------	----------

OMNITRONIC CNP-1 WLAN Multi-Room Streaming System

Type:	Wi-Fi
Power connection:	Mains input via USB, type B power supply cord with AC adapter (provided)
Frequency range:	20 - 20000 Hz
Control:	Wi-Fi
Frequency band:	2.4 GHz
Material:	Plastic
Dimensions:	Width: 12 cm Depth: 8,5 cm Height: 1,6 cm
Weight:	0,21 kg
Audio:	
Analog output:	3.5 mm stereo jack
Digital output:	Toslink SPDIF
Data transmission:	
WLAN standard:	IEEE 802.11g/b/n, 2.4 GHz
Ethernet/LAN:	10/100 mbit/s (RJ-45)
USB 2.0 host:	USB type A
Supported audio formats:	.aac, .ogg, .mp3, .flac, .alac, .ape, .wma, .wav, .au, .aif, .aiff, .m3u, .m4a, .asf, .mms (compressed/lossless)
Protocols:	UPnP/DLNA (DMR + DMS), AirPlay
Internet radio:	.aac, .mp3, .wma,
General:	
Power supply:	5 V DC, 500 mA via USB port or supplied PSU
Controls:	Power switch, reset button, LED indicators

OMNITRONIC C-50A active black 2x

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1 A fuse replaceable
Power:	Program: 80W Rated: 50W RMS
Frequency range:	50 - 20000 Hz
Sensitivity:	89 dB (1W/1m)
Attachment system:	Mounting bracket
Control elements:	Level control, tone control, power switch
Status LED:	Power
Connections:	Input: line via 1 x 3-pin XLR (F) mounting version Output: 1 x 3-pin XLR (M) mounting version
Speaker:	1 x woofer 5" Basket material: steel Conematerial: cardboard/paper 1 x tweeter 1"
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 18 cm Depth: 16,6 cm Height: 23 cm
Weight:	6,30 kg