

## OMNITRONIC Set 2x XKB-212A + Speaker Stand MOVE MK2

Active speaker set with 2x XKB-212A, 2x high-quality stands including bag, 2x XLR cable

Art. No.: 20000421

GTIN:



**List price: 855.61 €**

incl. 19% VAT.

### Features:

#### OMNITRONIC XKB-212A 2-Way Speaker, active, DSP

Active speaker with 12" woofer, 1,35" driver, HF: 60 W RMS, LF: 300 W RMS

- Active 12/2 full range system for mobile live and DJ applications
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Control via Bluetooth
- LCD display
- Digital signal processor
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL

#### Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord, 1 x declaration of conformity

### Logistic

#### OMNITRONIC Speaker Stand MOVE MK2 set

2 speaker stands, extendible up to 183 cm, maximum load 30 kg + carrying bag

- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height

### Package contents

- 1 x bag

### OMNITRONIC XLR cable 3pin 10m bk

Audio cable with 3-pin XLR connectors

- 1 x xLR cable

### Technical specifications:

#### OMNITRONIC XKB-212A 2-Way Speaker, active, DSP

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 600W Rated: 60W RMS HF Rated: 300W RMS LF
Frequency range:	55 - 20000 Hz
Sensitivity:	95 dB
DSP:	Digital signal processor
DSP presets:	LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
Control:	Bluetooth
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Display type:	LCD display
Control elements:	Master control, encoder
Controls:	Limiter
Status LED:	Power, signal, limit
Connections:	Output: line via 1 x 3-pin XLR
Input channels:	2 x mono with Mic-line switch via Combination socket (XLR/jack), channel control via Rotary dial
Equalizer:	Master: 1 x 3-band tone control
Speaker:	1 x woofer 12" Voice coil lows 2,4" with ferrit magnet Voice coil compression tweeter highs 1,35"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Material:	Plastic
Dimensions:	Width: 38 cm Depth: 35 cm Height: 61 cm
Weight:	15,45 kg

#### OMNITRONIC Speaker Stand MOVE MK2 set

Maximum carrying capacity:	30 kg
Tube diameter sector:	35
Height:	Maximum: 183 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel; Steel
Color:	Black
Weight:	5,10 kg

#### **OMNITRONIC XLR cable 3pin 10m bk**

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	460 g