



The article is no longer in our assortment.

Features:

ALUTRUSS Steel Base Plate round type A

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection set

Logistic

ALUTRUSS QUADLOCK End Plate QQGP-Male

- Trusspipe: 50 mm
- Made in Europe
- cone**
- M8 thread

EUROLITE FWH-37/70 Wall Mount for Monitors

Wall mount

- Wall mount for LCD monitors with a diagonal screen size of 939 mm (37") to 1778 mm (70")
- Stable metal version
- VESA standard up to 600 x 800 mm
- Adjustable tilt angle -5° to 15°
- Mounting materials included in the delivery

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

Package contents

- 2 x splint, 2 x bolt

Technical specifications:

Weight: 77,76 kg

ALUTRUSS Steel Base Plate round type A

Trusspipe:	50 mm
Material:	Steel
Color:	Alu colored
Dimensions:	Height: 1,60 cm Diameter: Ø 80 cm
Weight:	60 kg

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm

Width: 29 cm
Height: 29 cm

Weight: 10,80 kg

ALUTRUSS QUADLOCK End Plate QQGP-Male

Trusspipe: 50 mm

Color: Alu colored

Weight: 1,45 kg

Cone

Thread: M8 thread

EUROLITE FWH-37/70 Wall Mount for Monitors

Dimensions: Width: 85 cm
Depth: 9,5 cm
Height: 63 cm

Weight: 4,50 kg

Max Load WLL (4-fold): 60 kg

Max Load BGV C1 (8-fold): 30 kg

VESA: up to 600 x 800 mm

Distance to wall: 83 mm

Dimensions (LxHxW): 850 x 630 x 95 mm

EUROLITE TPC-10 Coupler, silver

Maximum load BGV C1 (8-fold): 75 kg

Maximum load WLL (4-fold): 150 kg

Tube diameter sector: 48 - 50 mm

Material: Aluminum

Color: Silver

Mounting screw: M10

Dimensions: Length: 10 cm
Width: 3 cm
Depth: 9 cm

Weight: 0,16 kg

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

Trusspipe: 50 mm

Color: Alu colored

Weight: 0,09 kg
