

EUROLITE Set 4x AKKU IP Flat Light 1 chrome + Soft Bag + Charger

4x flat spotlight with 15 W RGBW LED, soft bag and charger

Art. No.: 20000444

GTIN: 4026397628494



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Chrome housing
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 LED 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; DMX
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- OLED display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing
- <p>EUROLITE SB-14 Soft Bag
- <h2 class="featureSatz">Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights</h2>With 2 Outside pockets

Logistic

EAN / GTIN: 4026397628494

- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps
- <p>EUROLITE Charger 4x Akku Flat Light Series
- <h2 class="featureSatz">Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3</h2>

Technical specifications:

Weight: 7.34 kg

EUROLITE AKKU IP Flat Light 1 cr

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 22 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; DMX
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Chrome
Attachment system:	Mounting bracket
Display type:	OLED display
Dimensions:	Width: 17.2 cm Depth: 13.8 cm Height: 6.4 cm
Weight:	1.63 kg

Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-14 Soft Bag

Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Width: 28 cm Depth: 22 cm Height: 18 cm
Weight:	0.34 kg

EUROLITE Charger 4x Akku Flat Light Series

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 6000 mA
Power connection:	Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided)
Power output:	4 x coaxial power connector (F)
Weight:	0.49 kg

Scope of delivery:

4 x EUROLITE AKKU IP Flat Light 1 cr

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x battery
- 1 x declaration of conformity
- 1 x user manual

1 x EUROLITE Charger 4x Akku Flat Light Series

- 1 x charger
- 1 x power cord
- 1 x adapter cable