

EUROLITE Set LED KLS Laser Bar PRO FX Light Set + M-4 Speaker System 400000452

LED KLS Laser Bar PRO FX Light Set including aluminum speaker stand

GTIN







List price: 593.81 €

incl. 19% VAT.

Features: Logistic

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Laser; multi beam effect; flower effect; UV effect; strobe effect
- 39 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- Preprogrammed in EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; clubs/dancing school; mobile djs / entertainer; rental
- Application possibility: On stand

lase

 Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

 6 powerful LEDs 6 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately - With a beam angle of 13°

light effect

- 6 powerful LEDs 2 W high-power R/G/B
 spots controlled separately

hai

 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately

Package contents

1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 1 x foot control, 2 x knurled screw, 2 x washer, 2 x mounting bracket, 2 x battery, 1 x bag

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

Package contents

- 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 3,15 A
Lamp type:	LED lamp
DMX channels:	3; 5; 10; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
Preprogrammed in:	EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	2x mounting bracket
Dimensions:	Width: 1,030 cm
	Depth: 6,1 cm
	Height: 38,7 cm
Weight:	10,00 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable length:	3 m

Tromoto control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm
	Green (G) 30 mW 532nm
Light effect	
LED type:	6 x 2 W high-power R/G/B
Flash rate:	0 - 30 Hz
Spotlight	
LED type:	6 x 6 W high-power 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Bar	
LED type:	4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm
	Minimum: 140 cm
	Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13,5 cm
Weight:	3,30 kg