eurolite®

EUROLITE Set NSF-100 LED DMX Hybrid Spray Fogger + WRC-4 Wireless Remote@@onterol

DMX fog machine with 850 W and LED illumination including wireless control



List price: 272.51 €

incl. 19% VAT.

Features:

EUROLITE NSF-100 LED DMX Hybrid Spray Fogger

DMX fog machine with 850 W, LED illumination, vertical fog output

- Output nozzle with RGB LED illumination for impressive effect presentations
- Powerful, vertical fog output of 4 meters in rich RGB colors
- Additional button for manual activation
- Compact metal housing with carrying handle
- 9 powerful LEDs 3 W R/G/B
- Short warm-up time
- Output distance: Approx. 4 m
- Control via stand-alone; DMX; wireless remote control (optional)
- Color selection; color change adjustable
- Strobe effect
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With level indication
- Operates on water-based fluid
- Fixed, backlit tank
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; small rental
- Application possibility: Standing Package contents
- 1 x device, 1 x user manual, 1 x power cord

EUROLITE WRC-4 Wireless Remote Control with Receiver

Wireless remote control for NSF-100

Logistic

GTIN:

- Receiver and transmitter with on/off function **Package contents**
- 1 x receiver, 1 x remote control, 1 x declaration of conformity, 1 x battery

Technical specifications:

EUROLITE NSF-100 LED DMX Hybrid Spray Power supply: Power consumption: P classification: Power connection:	/ Fogger 230 V AC, 50 Hz 850 W IP20 Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power supply: Power consumption: P classification:	230 V AC, 50 Hz 850 W IP20 Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power supply: Power consumption: P classification:	230 V AC, 50 Hz 850 W IP20 Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power supply: Power consumption: P classification:	230 V AC, 50 Hz 850 W IP20 Mains input via IEC connector (M) mounting version power supply cord with safety plug
P classification:	IP20 Mains input via IEC connector (M) mounting version power supply cord with safety plug
	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power connection:	version power supply cord with safety plug
Fuse:	5 x 20 mm, F 5 A fuse replaceable
_ED type:	9 x 3 W R/G/B
Narm-up time:	Approx. 4 min
Output volume:	Approx. 500 m³/min
Output distance:	Approx. 4 m
Tank capacity:	0,9 I water-based fluid fixed, backlit tank
Fluid consumption:	Approx. 25 ml/min
DMX channels:	8
Control:	Stand-alone; DMX; wireless remote control (optional)
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Housing color:	Black
Display type:	Monochrome 4 digit 7-segment LED display
Controls:	Low fluid
Color:	Black
Dimensions:	Width: 25,5 cm Depth: 29 cm Height: 18,5 cm

	Depth: 29 cm Height: 18,5 cm
Weight:	5,00 kg
Noise classification:	Class 3 (clearly perceptible sounds)

EUROLITE WRC-4 Wireless Remote Control with Receiver

Battery:	1 x 12 V LR27 alkaline manganese built-in
Carrier frequency:	433,920 MHz
Weight:	0,11 kg