

EUROLITE Set 4x LED BAR-12 QCL RGBW Bar + Case

4x spotlight bar with 12 x 4 W 4in1 LED (RGBW) including flightcase

Art. No.: 20000461

GTIN:



List price: 927.01 €

incl. 19% VAT.

Features:

EUROLITE LED BAR-12 QCL RGBW Bar

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBW LED

- 12 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Application possibility: Suspended; wall mounting

Package contents

- 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

Logistic

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

Carrying case

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	22,30 kg
---------	----------

EUROLITE LED BAR-12 QCL RGBW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 110 cm Depth: 6,5 cm Height: 10 cm
Weight:	2,85 kg

Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm
Material:	Metal
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	108 cm x 44 cm x 7,5 cm
Device compartment:	108 cm x 6,5 cm x 7,5 cm
Dimensions:	Width: 117 cm Depth: 48 cm Height: 17 cm
Weight:	10,90 kg