

EUROLITE Set 4x AKKU Flat Light 3 sil + Charger + Case

4x flat spotlight with 3 x 8 W RGBW LED including charger and PRO flightcase

Art. No.: 20000477

GTIN:











The article is no longer in our assortment.

Features: Logistic

EUROLITE AKKU Flat Light 3 sil

Flat spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 12°
- With Mounting bracket
- Various versions available
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; Wedding/gala/events
- Dimmer curves with adjustable response; color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Preprogrammed in Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator

Package contents

 1 x device, 1 x user manual, 1 x external mains adapter, 1 x remote control, 1 x declaration of conformity, 1 x power cord

EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x Akku Flat Light 1/3Package contents

- 1 x charger, 1 x power cord, 1 x adapter cable

ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 11,12 kg	
------------------	--

EUROLITE AKKU Flat Light 3 sil

Protection class: Protection class: Protection class: Power connection: Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery pack type: 1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh Battery pack: Battery operation up to 16h depending on program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2,5 A
Protection class: Protection class III Power connection: Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery pack type: 1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh Battery pack: Battery operation up to 16h depending on program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 444; LED EASY OPERATOR 446; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Pin configuration:	Inside + / outside -
Power connection: Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery pack type: 1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh Battery pack: Battery operation up to 16h depending on program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	IP classification:	IP20
Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery pack type: 1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh Battery pack: Battery operation up to 16h depending on program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 2x4; LED EASY OPERATOR 2x5 SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Protection class:	Protection class III
Battery pack: Battery operation up to 16h depending on program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with Euro
program used Recharging time 4h Lamp type: LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Battery pack type:	1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh
LED lamp LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Battery pack:	, , , , ,
LED: 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz		Recharging time 4h
(homogenous color mix) DMX channels: 3; 4; 6; 8; 10 Cooling: Passive convection cooling Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light 'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Lamp type:	LED lamp
Cooling: Passive convection cooling Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	LED:	
Control: Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain; EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free 2,4 GHz	DMX channels:	3; 4; 6; 8; 10
Microphone; IR remote control Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free 2,4 GHz	Cooling:	Passive convection cooling
4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Carrier frequency: 2,4 GHz	Control:	·
Carrier frequency: 2,4 GHz	Preprogrammed in:	4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY
	Projection:	Flicker-free
Beam angle: 12°	Carrier frequency:	2,4 GHz
	Beam angle:	12°

Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Silver
Attachment system:	Mounting bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 16,8 cm
	Depth: 13,8 cm
	Height: 6,2 cm
Weight:	1,62 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Charger 4x Akku Flat Light Series

Power supply:	100-240 V AC, 50/60 Hz
	12,6 V DC 6 A
Power connection:	Mains input power supply cord with Euro plug (provided)
Power output:	4 x Coaxial power connector (F)
Weight:	490 g

ROADINGER Flightcase 4x AKKU Flat Light Series

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	7 cm x 18,5 cm x 9 cm
Accessory compartment:	38 cm x 6,5 cm x 12 cm
Inside dimensions:	38 cm x 25 cm x 12 cm
Dimensions:	Width: 42 cm
	Depth: 31 cm
	Height: 20 cm
Weight:	4,15 kg