

EUROLITE Set LED SL-350 DMX + Case

Follow spot with cold white 300 W LED including PRO flightcase

Art. No.: 20000483

GTIN:



List price: 2081.31 €

incl. 19% VAT.

Features:

EUROLITE LED SL-350 DMX Search Light

Follow spot with cold white 300 W LED for medium distances

- Manual control via control panel with buttons and faders
- 1 powerful LED 300 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With a beam angle of 10°
- With mounting bracket
- 4 digit 7-segment LED display
- Direct color temperature selection for 3 preset values
- Dimmer electronic
- Strobe effect
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Suitable for a range of use from to 30 meters
- Color wheel with 5 dichroic filters plus open
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x mounting bracket, 1 x hex key

Logistic

ROADINGER Flightcase SL-160/SL-350

Trunk case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	19,75 kg
---------	----------

EUROLITE LED SL-350 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 20 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	10°
Beam angle (1/2 peak):	10°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Range of use:	- 30m
Dimensions:	Length: 60 cm Width: 27,5 cm Height: 30 cm
Weight:	10,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase SL-160/SL-350

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; plywood multi-layer glued
Color:	Dark brown, laminated
Device compartment:	61 cm x 19,5 cm x 25 cm
Inside dimensions:	68 cm x 34 cm x 29 cm
Dimensions:	Width: 72 cm
	Depth: 38 cm
	Height: 34,5 cm
Weight:	9,20 kg