

EUROLITE Set LED Umbrella 140 + BS-2 EU

LED Umbrella with high steel speaker stand and adapter

Art. No.: 20000489

GTIN:



Features:

- DMX-controllable lighting effect umbrella with 114 SMD RGB LEDs, distributed in 7 segments
- Segments can be controlled individually via DMX
- 6 segments make the surface of the umbrella shine, one segment in the middle shines directly at the audience
- Perfect as stage background and eye-catcher for decorative purposes in shops, display windows, fair stands, hotels, bars and clubs
- Can be mounted to a lighting stand or trussing - the umbrella's angle can be adjusted
- Easy transport (can be folded), setup and installation
- Covers a large area with a diameter of 140 cm
- Built-in auto and music show programs
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Stepless RGB color mixture, dimmer and strobe effect
- Addressing via control panel with 4-digit LED display
- Appropriate control unit included in the delivery
- Power connection via P-Con jack and included power cable with safety plug
- 114 LEDs SMD 5050 3in1 R/G/B (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- <p>OMNITRONIC BS-2 EU Loudspeakerstand
- <h2 class="featureSatz">High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg</h2>Height adjustable, with locking pin
- Tube diameter: Ø 35 mm

Logistic

- Adjustable height
- Made in Europe
- <p>EUROLITE SPA-10S Adapter
- <h2 class="featureSatz">For 35 mm tube with screw thread and M10 wing bolt, max. load WLL 100 kg</h2>Adapter for installing a spot, speaker system etc. on a stand
- M10 wing bolt
- M10 thread

Technical specifications:

Weight: 8.35 kg

EUROLITE LED Umbrella 140

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 20 W |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED type: | 114 x SMD 5050 3in1 R/G/B (homogenous color mix) |
| DMX channels: | 6; 24 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light'J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Dimensions: | Diameter: Ø 140 cm |
| Weight: | 3.07 kg |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

OMNITRONIC BS-2 EU Loudspeakerstand

| | |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 50 kg |
| Height: | Maximum: 205 cm Minimum: 117 cm |
| Attachment system: | Ø 35mm |
| Type (general stands): | Speaker stand/manual |
| Material: | Steel |
| Color: | Black |
| Transport dimensions: | 110 cm x 17 cm x 14 cm |

Weight: 4.90 kg

EUROLITE SPA-10S Adapter

| | |
|-------------------------------|-----------------------------------|
| Maximum load BGV C1 (8-fold): | 50 kg |
| Maximum load WLL (4-fold): | 100 kg |
| Attachment system: | Ø 35mm |
| Type (general stands): | Accessory |
| Material: | Steel, powder-coated |
| Plate: | 1.3 cm Ø 6 cm |
| Thread: | M10 thread x 25 mm |
| Dimensions: | Height: 13 cm Diameter: Ø 6 cm |
| Weight: | 0.38 kg |

Scope of delivery:

1 x EUROLITE LED Umbrella 140

1 x omega bracket
1 x device
1 x user manual
1 x power cord
1 x multipin cable
1 x umbrella

1 x OMNITRONIC BS-2 EU Loudspeakerstand

1 x stand

1 x EUROLITE SPA-10S Adapter

1 x adapter
1 x user manual