



**The article is no longer in our assortment.**

### Features:

#### EUROLITE TMH XB-130 Moving-Head-Beam

Bright, extremely narrow beam with Osram Sirius HRI 132 W lamp

- 11 or 14 DMX channels selectable
- Very narrow beam angle of 1°
- Effect wheel with rotating 8-facet prism
- The prism rotates in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Frost filter
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 Volts
- Control board with LED display for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with master/slave function
- Software upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- With Osram Sirius HRI 132 W lamp
- Ready for connection via included IEC power cord with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX-control via any standard DMX-controller
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)

### Logistic

- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; Prism 8-fold; frost filter; Focus motor-driven
- Beam effect
- Color wheel with 14 dichroic filters plus open<BR>Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- With a beam angle of 1°
- OSRAM bulb included

**Package contents**

- 1 x omega bracket

**ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130**

PRO flightcase for 4 x PLB-130

- With 4 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Technical specifications:**

---

**EUROLITE TMH XB-130 Moving-Head-Beam**

|                     |  |
|---------------------|--|
| Power supply:       | 100-240 V AC, 50/60 Hz   |
| Power consumption:  | 170 W  |
| IP classification:  | IP20   |
| Power connection:   | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)       |
| Power output:       | 1 x IEC connector (F) mounting version   |
| Lamp type:          | Discharge lamp   |
| Max. TILT movement: | 270° Exact positioning (16 bit resolution) Auto position correction (feedback)                         |
| Max. PAN movement:  | 540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)                   |
| Flash rate:         | 0 - 20 Hz  |
| Equipment:          | Gobo wheel with static gobos; Prism 8-fold; frost filter; Focus motor-driven                           |
| Color generation:   | Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions |
| Gobos:              | Gobo wheel with static gobos, 17 gobos and open Shake effect   |
| DMX channels:       | 11; 14   |
| DMX input:          | 1 x 3-pin XLR (M) mounting version   |

|                        |   |
|------------------------|---|
| DMX output:            | 1 x 3-pin XLR (F) mounting version            |
| Cooling:               | Temperature-controlled fan                    |
| Control:               | Stand-alone; Sound to light via Microphone    |
| Preprogrammed in:      | LED PC-Control 512; Light Captain; Light´J    |
| Beam angle:            | 1°  |
| Beam angle (1/2 peak): | 1°  |
| Housing color:         | Black   |
| Use of brands:         | OSRAM bulb included                           |
| Dimensions:            | Width: 29 cm<br>Depth: 26 cm<br>Height: 40 cm |
| Weight:                | 10,65 kg                                      |

#### **ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 25 mm   |
| Case handle:             | 4 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                      |
| Transport aid:           | 4 x castors with 2 locking brakes             |
| Use of brands:           | Branded hardware                              |
| Material:                | Birch multiplex, 7 mm                         |
| Color:                   | Dark brown, laminated                         |
| Accessory compartment:   | 10 cm x 45 cm x 38,5 cm                       |
| Inside dimensions:       | 77 cm x 45 cm x 40,5 cm                       |
| Device compartment:      | 31,5 cm x 21,5 cm x 38,5 cm                   |
| Dimensions:              | Width: 81 cm<br>Depth: 50 cm<br>Height: 43 cm |
| Weight:                  | 22,60 kg                                      |