

EUROLITE Party-Accu-Camping Set

Battery powered party set with portable PA system and 3 lighting effects

Art. No.: 20000498

GTIN:



The article is no longer in our assortment.

Features:

- Portable all-in-one PA system with 40 watts output power
- 4-channel mixer
- 2-way bass-reflex system
- SD card slot and USB port
- 1 microphone input (XLR) with adjustable reverb effect
- UHF receiver unit and matching wireless microphone
- Power-efficient and battery-saving class D amplifier
- Tone control and master control
- Integrated automatic charging of the battery
- The device is cooled by passive convection cooling
- UHF 863 - 865 MHz License-free and approved in Europe
- Black metal grille
- Rugged carrying handle
- For application areas such as: Theater; mobile use; wedding/gala/events; product presentations and lectures

battery pack

- Battery pack must be ordered separately
- Cordless, flexible and versatile
- Battery operation up to 4h

audio player

- Control via Bluetooth; IR remote control
- Bluetooth: operating range up to 10m
- 2.4 GHz license-free worldwide
- 4 digit 7-segment LED display

microphone

- Polar pattern: Cardioid

Logistic

- Operating range up to 30m
- remote control**
- Operating range up to 10m
- <p>EUROLITE AKKU Mini PARty RGBW Spot
- <h2 class="featureSatz">DMX spotlight with 12 x 1 W LED in the colors red, green, blue and white</h2>Equipped with twelve 1 W LEDs - 3 x red, 3 x green, 3 x blue and 3 x white
- Small and compact, easy to transport, ideal for mobile use
- Operation via built-in rechargeable lithium-ion battery with min. 3 hours operating time
- Built-in auto and music show programs
- Functions: static colors, RGBW color mixture, internal programs, color change with diverse settings, dimmer and strobe settings
- Addressing via control panel with 4-digit LED display
- Additional controlling possibility via EUROLITE IR-25 remote control; included in delivery
- Built-in charging function via included USB charger
- Can also be charged via USB power banks
- Mounting bracket for ceiling or wall mounting
- Additional bracket for floor use
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LEDs 1 W SMD 8072 R/G/B/W (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- With a beam angle of 12°
- 4 digit 7-segment LED display
- For application areas such as: Gift idea

device

- Cordless, flexible and versatile
- Battery operation up to 3h depending on program used
- <p>EUROLITE AKKU BEL-15 Beam tc
- <h2 class="featureSatz">Handy battery-powered beam effect with up to 5 beams, transparent housing</h2>Powerful battery-powered beam effect in a pocket housing
- Cordless, flexible and versatile
- Battery operation up to 4h
- 5 LEDs 3 W high-power R/G/B/W/A
- Color change adjustable; color fade adjustable
- Multi beam effect; strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; sound to light via microphone
- With mounting bracket
- <p>EUROLITE AKKU BEK-10 Kaleidoscope tc
- <h2 class="featureSatz">Handy battery-powered kaleidoscope effect, transparent housing</h2>Powerful battery-powered Kaleidoscope Effect in a pocket housing
- Equipped with one bright 4in1 LED with 10 W in the colors red, green, blue, white
- Ideal for mobile use thanks to quick setup and rechargeable lithium-ion battery pack (up to 4 hours operating time)
- Transparent white plastic housing with plastic bracket
- Functions: Auto mode, automatic color change, fading colors, strobe effect
- Charger included in delivery
- Switch-mode power supply for operation between 100 and 240 volts
- 1 LED 10 W high-power 4in1 RGBW
- Flower effect; gobo effect
- The device is cooled by passive convection cooling
- Control via IR remote control; sound to light via microphone

device

- Cordless, flexible and versatile
- Battery operation up to 4h depending on program used

Technical specifications:

Weight:

6.70 kg

OMNITRONIC WAMS-65BT Wireless PA System

| | |
|-----------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz Or 12V DC |
| Power consumption: | 60 W |
| Protection class: | Protection class I |
| Output power: | 40 W RMS |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack (not included) |
| Frequency range: | 62 - 18000 Hz |
| THD: | <0.5 % at 1 kHz |
| Cooling: | Passive convection cooling |
| Frequency band: | UHF 863 - 865 MHz |
| Carrier frequency: | 865 MHz |
| Frequency stability: | ± 0.005 % |
| Frequency selection: | Fixed frequencies |
| Housing color: | Black |
| Attachment system: | Flange: Ø 35mm |
| Circuitry: | Class D |
| Control elements: | Echo effect control, audio player |
| Status LED: | Power, peak, ON AIR, signal, charge status indicator |
| Connections: | Input: microphone via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 6.3 mm plug (unbal.) |
| Channels: | Microphone channel: 1 x mono via XLR, channel control via rotary dial Input channel: 1 x stereo via RCA, channel control via rotary dial Input channel: 1 x stereo via audio player, channel control via rotary dial Input channel: 1 x mono via radio, channel control via rotary dial Master output: 1 x mono, channel control via rotary dial, tone control EQ |
| Speaker: | 1 x woofer 6.5" 1 x tweeter 1" |
| Type of speaker: | Compact cabinet speaker; wireless PA system |
| Type of construction: | Vented |
| Carrying handle: | 1 pc/pcs |
| Material: | ABS Acrylonitrile butadiene styrene |
| Color: | Black |
| Dimensions: | Width: 23.5 cm Depth: 22 cm Height: 35 cm |
| Weight: | 4.15 kg |

| | |
|--------------------------|---|
| Power supply: | 3V DC |
| Power connection: | Battery/battery pack |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Battery: | 2 x Mignon (AA) (not included) |
| Range: | Range up to 30m |
| RF power output: | 10 mW |
| Modulation: | FM |
| Switch: | On/off/mute switch |
| Material: | Plastic |
| Dimensions: | Length: 26 cm Diameter: Ø 4 cm |
| Weight: | 0.115 kg |
| Control: | Bluetooth; IR remote control |
| Bluetooth device name: | Omnitronic |
| Audio player: | USB + SD + Bluetooth |
| Range: | Bluetooth: range up to 10m |
| Frequency band: | 2.4 GHz |
| Display type: | 4 digit 7-segment LED display |
| Music format: | MP3, WAV |
| Available storage media: | USB devices/SD cards max. 32GB (FAT 32) |
| Power supply: | 3V DC |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Range: | Range up to 10m |
| Battery pack type: | 1 x lead 12 V, 2900 mAh, |
| Battery pack: | Battery operation up to 4h Recharging time 4h |

Akku 12V/2900mAh WAMS-05 / WAMS-65

| | |
|---------|----------|
| Weight: | 1.094 kg |
|---------|----------|

EUROLITE AKKU Mini PARTy RGBW Spot

| | |
|--------------------|--|
| Power supply: | 5V DC |
| Power consumption: | 10 W |
| Power connection: | Battery/battery pack Mains input via micro USB (F) mounting version power supply cord with AC adapter (provided) |
| Lamp type: | LED lamp |
| LED type: | 12 x 1 W SMD 8072 R/G/B/W (homogenous color mix) |
| DMX channels: | 6 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |

| | |
|-------------------------|---|
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function |
| Fixtures available for: | Light´J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE |
| Beam angle (1/2 peak): | 12° |
| Beam angle (1/10 peak): | 27° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 16.2 cm Depth: 11.7 cm Height: 13.3 cm |
| Weight: | 0.60 kg |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Battery pack type: | 1 x lithium ion 3.7 V, 2000 mAh, 7.4 Wh |
| Battery pack: | Battery operation up to 3h depending on program used Recharging time 3h |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE AKKU BEL-15 Beam tc

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 3.7V DC 2200 mA |
| Power consumption: | 9.2 W |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Battery pack type: | 1 x lithium ion 3.7 V, 2200 mAh, 8 Wh |
| Battery pack: | Battery operation up to 4h Recharging time 4.5h |
| Lamp type: | LED lamp |
| LED type: | 5 x 3 W high-power R/G/B/W/A |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; IR remote control; sound to light via microphone |
| Housing color: | Clear |
| Attachment system: | Mounting bracket |
| Dimensions: | Width: 14.6 cm Depth: 15.5 cm Height: 15 cm |
| Weight: | 0.39 kg |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE AKKU BEK-10 Kaleidoscope tc

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz 3.7V AC 2200 mA |
| Pin configuration: | Inside + / outside - |
| Power consumption: | 9.2 W |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Lamp type: | LED lamp |
| LED type: | 1 x 10 W high-power 4in1 RGBW |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; sound to light via microphone |
| Housing color: | Clear |
| Dimensions: | Width: 14.6 cm Depth: 15.5 cm Height: 11.5 cm |
| Weight: | 0.46 kg |
| Battery pack type: | 1 x lithium ion 3.7 V, 2200 mAh, 8 Wh |
| Battery pack: | Battery operation up to 4h depending on program used Recharging time 4.5h |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x OMNITRONIC WAMS-65BT Wireless PA System

1 x device
1 x power cord
1 x microphone
1 x remote control
1 x user manual
1 x declaration of conformity

1 x Akku 12V/2900mAh WAMS-05 / WAMS-65

1 x device

1 x EUROLITE AKKU Mini PARTY RGBW Spot

1 x spotlight
1 x user manual
1 x external mains adapter
1 x remote control
1 x battery

1 x EUROLITE AKKU BEL-15 Beam tc

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x user manual

1 x EUROLITE AKKU BEK-10 Kaleidoscope tc

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x user manual