

PSSO®

Prime Set XL

Art. No.: 20000514

GTIN:



All rights reserved. Subject to change without notice. Errors and omissions excepted.
Illustration only. Actual item may differ from photo.

PSSO®

Prime Set XL

Art. No.: 20000514

GTIN:

Features:

PSSO PRIME-212 Club Speaker System

PRO PA speaker, 2 x 12" woofer, 1.5" horn, 1100 W RMS (Biamp)

- Rugged pro PA speaker, qualified for suspension and clubs
- Biamp operation
- Housing made of 18 mm (13 layers) and 25 mm (17 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.5"), 72 mm voice coil (2.8")
- Bassreflex system
- Neutrik Speakon connectors
- Scratch-resistant lacquer surface
- Applications: standing or suspended
- CELTO ACOUSTIQUE driver
- European engineering

PSSO PRIME-182 Subwoofer 3000W

PRO PA bassreflex subwoofer, 2 x 18" woofer, 3000 W RMS, 4 ohms

- Rugged pro bassreflex subwoofer, qualified for clubs and touring applications
- Housing made of 25 mm (17 layers) and 18 mm (13 layers) birch plywood
- 2 x 45 cm (18") bass speaker, 115 mm voice coil (4.5"), diecast aluminum basket
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Parallel Neutrik Speakon connectors
- Metal flange for top speakers
- Carrying handles and rubber feet
- Scratch-resistant lacquer surface
- CELTO ACOUSTIQUE driver
- European engineering

PSSO PRIME System Amplifier DSP

Class D multi-channel PA amplifier with SMPS, 4 x 400 W RMS (8 ohms), 4 x 800 W RMS (4 ohms)

- 6-channel PA amplifier with high-performance DSP, freely programmable
- Sample frequency: 96 kHz and 64-bit technology
- Premium components ensure excellent sound features
- Efficient class D amplifier circuitry
- 2 Pascal amplifier modules
- 4 analog inputs and 2 digital AES/EBU interfaces (XLR)
- 4 analog link outputs (XLR)
- 2 Neutrik Speakon outputs