



The article is no longer in our assortment.

Features:

EUROLITE LED KLS-801 Compact Light Set

Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix) spots controlled separately

Logistic

- Control via stand-alone; DMX; Foot switch (optional); Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 30°
- TV spigot
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x spotlight, 1 x bag

EUROLITE STV-50-WOT EU Steel stand

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Made in Europe

Package contents

- 1 x user manual

Technical specifications:

Weight:	17,25 kg
---------	----------

EUROLITE LED KLS-801 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	90,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED:	7 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; Foot switch (optional); Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11,75 kg
Spotlight	
Dimensions:	Width: 1,2 m

