

OMNITRONIC Set BOB-10A bk + 2x BOB-4 bk

BOB-10A Subwoofer active including 2 x 4" satellite speakers BOB-4

Art. No.: 2000532

GTIN:

**List price: 617.61 €**

incl. 19% VAT.

Features:**Logistic****OMNITRONIC BOB-10A Subwoofer active black**

10" subwoofer with DSP and Bluetooth for the BOB series

- 10" bassreflex subwoofer with DSP and 900 watts RMS power
- Flexibly extendable with BOB-4 satellites for 2.1, 4.1 and 8.1 configurations
- DSP-controlled class D amplifier (300 W + 2 x 300 W)
- Integrated Bluetooth audio streaming
- 4 EQ presets with indicators
- Signal limiter and crossover
- Signal inputs via combo jacks (XLR/6.3 mm jack) and RCA
- Parallel XLR outputs for linking further BOB systems or active systems
- Separate volume controls for subwoofer and satellites L/R
- Stereo/mono selection
- Phase reversal switch
- Fault, limit, signal and power indicators
- Built-in protection circuits: soft start, short-circuit, limiter, overcurrent, overheat
- Two M20 metal flanges for mounting satellite speakers
- MDF enclosure (15 mm) with scratch-resistant lacquer surface and metal grille
- Built-in handles and low weight for ease of transport
- Stackable via recesses when set up horizontally
- Delivery includes two speaker cables
- For mobile live and DJ applications and installation in bars, stores, conference rooms and home theaters
- Digital signal processor
- Controlling by Bluetooth

OMNITRONIC BOB-4 Top 16 Ohm black 2x

2 x 4" satellite speakers with bracket for the BOB series

- 16-ohm speaker pair with 4" full-range speaker
- For use with BOB-10A subwoofers for 2.1, 4.1 and 8.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers
- Rated power: 75 W RMS/150 W program
- Connectors: 1 x speaker and screw plug terminal
- Light-weight plastic cabinet with M8 and M10 threaded inserts
- Scratch-resistant lacquer surface and steel grille
- Transport bag for 4 satellites, brackets and cables optional
- With Mounting bracket
- With Mounting bracket

Technical specifications:

Weight: 20,30 kg

OMNITRONIC BOB-10A Subwoofer active black

Power supply:	230 V AC, 50 Hz
Power consumption:	1060 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Rated power:	1 x 300 W RMS LF; 2 x 300 W RMS HF
Frequency range:	45 - 250 Hz
Sensitivity:	100 dB
Max. SPL:	125 dB
DSP:	Digital signal processor
Control:	Bluetooth
Attachment system:	M20 thread
Circuitry:	Class D
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: speakers via 2 x speaker built-in socket (F) Output: line via 2 x 3-pin XLR
Input channels:	1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial
Speakers:	1 x woofer (10") approx. 25 cm Voice coil lows (2") approx. 5 cm
Type of speaker:	Subwoofer
Type:	Vented
Material:	MDF (Medium-density fibreboard)
Color:	Black
Dimensions:	Width: 30 cm Depth: 47 cm

Height: 43 cm

Weight: 16,30 kg

OMNITRONIC BOB-4 Top 16 Ohm black 2x

Rated power: 75 W RMS

Program power: 150 W

Frequency range: 150 - 16000 Hz

Sensitivity: 90 dB (1W/1m)

Max. SPL: 109 dB

Impedance: 16 ohms

Attachment system: Mounting bracket
2x Mounting bracket

Connections: Input: speakers via 1 x screw terminal
Input: speakers via 1 x speaker built-in socket (F)

Speakers: 1 x compression tweeter highs (4") approx. 10 cm
1 x Voice coil compression tweeter highs (1")
approx. 2,5 cm

Color: Black, painted

Dimensions: Width: 15 cm
Depth: 16 cm
Height: 15,8 cm

Weight: 4,00 kg
