eurolite®

EUROLITE Set 4x LED Umbrella 95 + Case

4x LED Umbrella 95 including flightcase with castors

Art. No.: 20000542

GTIN:

The article is no longer in our assortment.

Features:

EUROLITE LED Umbrella 95

Extraordinary RGB eye-catcher

- 114 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
7 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- Easy to assemble
- 3 digit 7-segment LED display
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; clubs/dancing school; restaurants, bars and hotels; stage
- Application possibility: Suspended; on stand
    Package contents
- 1 x omega bracket, 1 x device, 1 x user manual, 1 x power cord, 1 x multipin cable, 1 x umbrella

ROADINGER Flightcase 4x LED Umbrella

Trunk case with castors

- With 4 device compartments

Logistic

- High-quality workmanship with plywood multi-layer glued 7 mm, red, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	29,22 kg

EUROLITE LED Umbrella 95

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
LED type:	114 x SMD 5050 3in1 TCL RGB (homogenous color mix)
DMX channels:	6; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Setup:	Easy to assemble
Housing color:	Black
Display type:	3 digit 7-segment LED display
Weight:	2,68 kg
Umbrella	
Dimensions:	Diameter: Ø 95 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED Umbrella

Maximum load:	100 kg

Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 7 mm
Color:	Red, laminated
Accessory compartment:	98,5 cm x 12,5 cm x 20 cm
Device compartment:	18,5 cm x 24 cm x 20 cm
Inside dimensions:	92,5 cm x 36,5 cm x 20 cm
Dimensions:	Width: 104 cm Depth: 43 cm Height: 41 cm
Weight:	18,50 kg