

FUTURELIGHT Set 2x DMH-200 LED Moving-Head + Case

Art. No.: 2000544

2x PRO beam/wash Moving Head with 200 W COB LED including flightcase with wheels

GTIN:



List price: 5115.81 €

incl. 19% VAT.

Features:

FUTURELIGHT DMH-200 LED Moving Head

PRO beam/wash moving-head with 200 W COB LED and large zoom

- Equipped with a powerful white 200 W COB LED
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism
- Exact positioning via 16-bit PAN/TILT movement resolution
- Motorized focus
- Autofocus
- Motorized zoom with 7.5-40° beam angle
- Steplessly adjustable iris
- Stepless frost-filter
- Electronic dimmer (0-100%)
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Control panel with LC display for easy configuration
- Stand-alone, master/slave and DMX mode
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- LED: 1 x COB (chip-on-board) 200 W cold white (CW)

Logistic

- Color wheel 8 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for exchanging gobos without tools
- Can be operated in 15; 17; 24; 25 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain
- Flicker-free projection
- Effect: Gobo effect; Single Beam

ROADINGER Flightcase 2x DMH-200 LED

PRO Flightcase for 2 x FUTURELIGHT DMH-200 LED

- Suitable for two devices and accessories
- Additional accessory compartment
- 4 castors Ø100 mm, 2 of which with locking brakes
- For optimal security
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- With castors
- With 4 built-in stacking trays in the cover
- Made in Europe

Technical specifications:

FUTURELIGHT DMH-200 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	270 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 200 W cold white (CW)
Max. TILT movement:	Exact positioning (16 bit resolution) 265° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; Prism 3-fold; Iris; Focus motor-driven; Zoom motor-driven; frost filter
Color generation:	Color wheel 8 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 7 gobos and open Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 27mm

Image diameter 22mm
Shake effect
Gobos changeable
Slot-in gobo system for exchanging gobos without tools

DMX channels:	15; 17; 24; 25
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Sound to light via Microphone; LED PC-Control 512; Light Captain
Beam angle:	7,5 - 40°
Beam angle (1/2 peak):	7,5 - 40°
Beam angle (1/10 peak):	7,5 - 40°
Housing color:	Black
Dimensions:	Width: 40,2 cm Depth: 25 cm Height: 53,4 cm
Weight:	21,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x DMH-200 LED

Aluminum profile frames:	30 mm
Case handles:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Castors 4 x built-in stacking trays in the cover
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	11,5 cm x 58 cm x 38 cm
Device compartment:	25 cm x 58 cm x 56,5 cm
Inside dimensions:	58 cm x 38 cm
Dimensions:	Width: 96 cm Depth: 60 cm Height: 89 cm
Weight:	33,50 kg