

FUTURELIGHT Set 4x DMH-200 LED Moving-Head + Case

4x PRO beam/wash moving head with 200 W COB LED including flightcase with wheels

Art. No.: 20000545

GTIN:



The article is no longer in our assortment.

Features:

FUTURELIGHT DMH-200 LED Moving Head

PRO beam/wash moving head with 200 W COB LED and large zoom

- Effect wheel with rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Steplessly adjustable iris
- Stepless frost-filter
- Electronic dimmer (0-100%)
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 1 powerful LED 200 W COB (chip-on-board) cold white (CW)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; iris; focus motor-driven; zoom motor driven; frost filter
- Gobo effect; beam effect
- Color wheel with 8 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect

Logistic

- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- Flicker-free
- With a beam angle of 7,5° - 40°

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x mounting bracket, 1 x XLR cable

ROADINGER Flightcase 4x DMH-200 LED

Trunk case with castors

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT DMH-200 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	270 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	265° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; iris; focus motor-driven; zoom motor driven; frost filter
Color generation:	Color wheel with 8 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 27mm Image diameter 22mm Shake effect

	Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	15; 17; 24; 25
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light'J
Projection:	Flicker-free
Beam angle:	7,5° - 40°
Beam angle (1/2 peak):	7,5 - 40°
Beam angle (1/10 peak):	7,5 - 40°
Housing color:	Black
Dimensions:	Width: 40,2 cm Depth: 25 cm Height: 53,4 cm
Weight:	21,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x DMH-200 LED

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	92 cm x 28 cm
Device compartment:	37,5 cm x 23,5 cm x 54 cm
Inside dimensions:	92 cm x 54 cm
Dimensions:	Width: 96 cm Depth: 96 cm Height: 88,5 cm
Weight:	51,65 kg