

## EUROLITE Set 4x AKKU IP UP-4 QCL Spot QuickDMX + Case with charging function 0546

4x weatherproof Uplight with 4 x 10 W 4in1 LED including PRO flightcase with charging function

GTIN:



**List price: 2200.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

Weather-proof (IP65), Uplight with 4 x 10 W 4in1 LED, QuickDMX & diffusor disk

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless and versatile
- 4 high-power 10 W RGBW LEDs (4in1)
- For indoor and outdoor use (IP65)
- Additional milky diffuser provides a soft, homogeneous light
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 16 hours operating time
- Wireless master/slave operation via QuickDMX
- Integrated automatic charging of the battery with indicator
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- LC display with touch buttons for easy configuration
- Kensington security slot for anti-theft protection
- Folding foot for angled placement
- LED: 4 x high-power 10 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection
- Controlling by stand-alone; DMX; QuickDMX built-in; Sound to light via Microphone; IR remote control
- Preprogrammed in Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free projection
- Suitable for outdoor use
- With a KENSINGTON LOCK theft protection

### Logistic

- For application areas such as: Small lender; Wedding/gala

### ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function

PRO flightcase for 4 x AKKU IP UP-4 QCL Spot QuickDMX, with charging function

- Suitable for four EUROLITE AKKU IP UP-4 QCL Spot QuickDMX (No. 41700542)
- Charges up to four spots
- 4 castors, 2 of which with locking brakes
- Power connection via P-Con jack and included power cable
- With accessory compartment
- High-quality workmanship with plywood glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- With castors
- With 4 built-in stacking trays in the cover

### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 32,81 kg |
|---------|----------|

### EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

|                        |   |
|------------------------|---|
| Power supply:          | 100-240 V AC, 50/60 Hz  |
| IP classification:     | IP65  |
| Protection class:      | Class I   |
| Power connection:      | Battery/battery pack<br>Mains input via IP P-Con (Power in) yellow mounting version power supply cord with safety plug (provided)   |
| Cable length:          | Approx. 1,2 m   |
| Battery pack type:     | 1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh   |
| Battery pack:          | Battery operation up to 16h depending on program used<br>Recharging time 3h   |
| Lamp type:             | LED lamp  |
| LED:                   | 4 x high-power 10 W 4in1 QCL RGBW (homogenous color mix)  |
| DMX channels:          | 3; 4; 6; 8; 10  |
| DMX input:             | 1 x 3-pin XLR (M) mounting version IP   |
| DMX output:            | 1 x 3-pin XLR (F) mounting version IP   |
| Cooling:               | Passive convection  |
| Control:               | Stand-alone; DMX; QuickDMX built-in; Sound to light via Microphone; IR remote control; Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Beam angle:            | 7°  |
| Beam angle (1/2 peak): | 7°  |

|                         |   |
|-------------------------|---|
| Beam angle (1/10 peak): | 20°   |
| Housing color:          | Black   |
| Display type:           | LCD display   |
| Carrier frequency:      | 2,4 GHz   |
| Theft protection:       | KENSINGTON LOCK   |
| Dimensions:             | Width: 15 cm<br>Depth: 18 cm<br>Height: 19,8 cm         |
| Weight:                 | 4,44 kg   |
| Noise classification:   | Class 0 (no noise at all)                               |
| Remote control          |   |
| Battery:                | 1 x Button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination            |
| Intended use:           | Show effect lighting                                    |

#### **ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

|                          |  |
|--------------------------|--|
| Power supply:            | 100-240 V AC, 50/60 Hz   |
| Power consumption:       | Max. 1150 W  |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Device fuse:             | 5 x 20 mm, F 5 A Fuse replaceable  |
| Aluminum profile frames: | 25 mm  |
| Case handles:            | 2 pc/pcs   |
| Stop hinge:              | 2 pc/pcs   |
| Lock:                    | Butterfly lock: 2 pc/pcs   |
| Transport aid:           | Castors<br>4 x built-in stacking trays in the cover  |
| Material:                | Plywood glued, 9 mm; birch multiplex   |
| Color:                   | Black, laminated   |
| Compartment dimensions:  | 18 cm x 15,5 cm x 14 cm  |
| Accessory compartment:   | 7 cm x 43 cm x 14 cm   |
| Inside dimensions:       | 56 cm x 43 cm x 20 cm  |
| Dimensions:              | Width: 60 cm<br>Depth: 47 cm<br>Height: 37,5 cm  |
| Weight:                  | 15,05 kg   |