

## EUROLITE Set LED Strip RGBWW 5m + DMX Controller + Transformer 24V Art. No.: 20000552

Flexible LED strip with RGB and warm white LEDs incl. controller and transformer 24V

GTIN:



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED Strip 300 5m RGBWW 24V

Flexible LED strip with RGB and warm white LEDs

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 powerful LEDs SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
- Control via system controller
- Good color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

#### Package contents

- 1 x illuminant, 1 x user manual

### Logistic

#### EUROLITE LED Strip RGBW 4-channel DMX Controller

4-channel LED controller with DMX interface for RGB LEDs 12-24 V

- Compact LED controller for controlling RGBW LEDs (12-24 V) via DMX
- Converts standard DMX512 signals to PWM signals e.g. for driving LED strips
- 4 separate control channels for individual color mixing of red, green, blue and white LEDs
- Switchable termination resistor

- Plug-in screw terminals for connecting the LEDs and the power supply
  - RJ45 jacks for serial connection
  - Rugged black metal housing
  - Integrated show programs
  - Control via stand-alone
  - For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels
  - Silent operation
- Package contents**
- 1 x device, 1 x user manual

#### **EUROLITE Electr. LED Transformer, 24V, 5A, IP67**

Stabilized LED power supply unit DC 24 V, 5 A

- Especially for LED installations
  - For indoors and outdoors (IP67)
  - Input voltage AC 100-240 V
  - Output voltage DC 24 V, 5 A
  - Protected against short circuit, overload, overheating and overvoltage
  - Noise filter
  - Connection via bare cable ends
  - L x W x H: 200 x 50 x 36 mm
  - 600 g
- Package contents**
- 1 x external mains adapter

#### **Technical specifications:**

---

Weight:	1,02 kg
---------	---------

---

#### **EUROLITE LED Strip 300 5m RGBWW 24V**

Power supply:	24V DC
Power consumption:	67 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,15 m
LED type:	300 x SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Color rendering index (CRI):	82 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	13,4 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	10 cm
Housing color:	White
Dimensions:	Length: 500 cm Width: 1,2 cm

	Height: 0,2 cm
Weight:	0,15 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

#### **EUROLITE LED Strip RGBW 4-channel DMX Controller**

Power supply:	12/24V DC
Power consumption:	Max. 384 W 12 V DC Max. 768 W 24 V DC Max. 96 W 12 V DC per channel Max. 192 W 24 V DC per channel
Output current:	Max. 4 x 8 A per channel
Power connection:	Via screw terminal
Power output:	Screw terminal
DMX channels:	4
DMX input:	3-pin XLR (M) mounting version 1 x RJ-45 (F) mounting version
DMX output:	3-pin XLR (F) mounting version RJ-45 (F) mounting version
Control:	Stand-alone
Dimensions:	Length: 16,4 cm Width: 6,6 cm Height: 3,8 cm
Weight:	0,30 kg
Noise classification:	Class 0 (no noise at all)

#### **EUROLITE Electr. LED Transformer, 24V, 5A, IP67**

Power connection:	Fixed supply cord with open wires
Power output:	1 x no connector/cable only
Dimensions:	Width: 5 cm Depth: 20 cm Height: 3,6 cm
Weight:	0,58 kg