



### Features:

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 LEDs SMD 5050 4in1 RGB/WW (homogenous color mix)
- Control via system controller
- Good color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
- <p>EUROLITE LED Strip RGBW 4-channel DMX Controller
- <h2 class="featureSatz">4-channel LED controller with DMX interface for RGB LEDs 12-24 V</h2>Compact LED controller for controlling RGBW LEDs (12-24 V) via DMX
- Converts standard DMX512 signals to PWM signals e.g. for driving LED strips
- 4 separate control channels for individual color mixing of red, green, blue and white LEDs
- Switchable termination resistor
- Plug-in screw terminals for connecting the LEDs and the power supply
- RJ45 jacks for serial connection
- Rugged black metal housing
- Integrated show programs
- Control via stand-alone
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels

### Logistic

- Silent operation
- <p>EUROLITE Electr. LED Transformer, 24V, 5A, IP67
- <h2 class="featureSatz">Stabilized LED power supply unit DC 24 V, 5 A</h2>Especially for LED installations
- For indoors and outdoors (IP67)
- Input voltage AC 100-240 V
- Output voltage DC 24 V, 5 A
- Protected against short circuit, overload, overheating and overvoltage
- Noise filter
- Connection via bare cable ends
- L x W x H: 200 x 50 x 36 mm
- 600 g

## Technical specifications:

---

Weight: 1.02 kg

---

### EUROLITE LED Strip 300 5m RGBWW 24V

Power supply:	24V DC
Power consumption:	67 W
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.15 m
Lamp type:	LED lamp
LED type:	300 x SMD 5050 4in1 RGB/WW (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Color rendering index (CRI):	82 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	13.4 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	10 cm
Housing color:	White
Dimensions:	Length: 500 cm Width: 1.2 cm Height: 0.2 cm
Weight:	0.15 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

### EUROLITE LED Strip RGBW 4-channel DMX Controller

Power supply:	12/24V DC
Power consumption:	Max. 384 W 12 V DC

Max. 768 W 24 V DC  
Max. 96 W 12 V DC per channel  
Max. 192 W 24 V DC per channel

Output current:	Max. 4 x 8 A per channel
Power connection:	Via screw terminal
Power output:	Screw terminal
DMX channels:	4
DMX input:	3-pin XLR (M) mounting version 1 x RJ-45 (F) mounting version
DMX output:	3-pin XLR (F) mounting version RJ-45 (F) mounting version
Control:	Stand-alone
Dimensions:	Length: 16.4 cm Width: 6.6 cm Height: 3.8 cm
Weight:	0.30 kg
Noise classification:	Class 0 (no noise at all)

#### **EUROLITE Electr. LED Transformer, 24V, 5A, IP67**

Power connection:	Fixed supply cord with open wires
Power output:	1 x no connector/cable only
Dimensions:	Width: 5 cm Depth: 20 cm Height: 3.6 cm
Weight:	0.58 kg

#### **Scope of delivery:**

##### **1 x EUROLITE LED Strip 300 5m RGBWW 24V**

1 x illuminant  
1 x user manual

##### **1 x EUROLITE LED Strip RGBW 4-channel DMX Controller**

1 x device  
1 x user manual

##### **1 x EUROLITE Electr. LED Transformer, 24V, 5A, IP67**

1 x external mains adapter