eurolite

EUROLITE Set LED Strip 2700K 5m + 2x Controller Zone + 2x Transformer 12. Wo.: 20000553 GTIN:

LED Strip 5m, 2x Controller Zone and 2x Transformer 12V



The article is no longer in our assortment.

Features:

EUROLITE LED Strip 300 5m 3528 2700K 12V

Flexible LED strip with a CRI >90

- Flexible LED strip for decorative lighting -
- High-grade components and a solid construction guarantee a long service life and excellent _ color rendering
- Can be cut into segments of variable size -
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 powerful LEDs SMD 3528 warm white (WW)
- Control via accessory
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation;
- restaurants, bars and hotels
- Silent operation

Package contents 1 x illuminant, 1 x user manual

EUROLITE LED Strip Receiver Zone Single Color

Wireless receiver for controlling single-colored LED strips 12-24 V

- For dimming single-colored LED strips 12-24 V
- 2 channels

Logistic

EUROLITE LED Strip Remote Control Zone Single Color

Wireless remote control for single-colored LED strips 12-24 V

- Controls 4 zones
- Multiple remote controls possible in one zone
- Powered by a battery/battery pack
- Dimmer electronic
- Operating range up to 30m

EUROLITE Electr. LED Transformer, 12V, 4A

Stabilized LED power supply unit DC 12 V, 4 A

- Especially for LED installations
 Input voltage AC 100-240 V
- Package contents
- 1 x external mains adapter

Technical specifications:

Weight:

0,66 kg

EUROLITE LED Strip 300 5m 3528 2700K 12V

Power supply:	12V DC
Power consumption:	18 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
LED type:	300 x SMD 3528 warm white (WW)
Control:	Accessory
Standing/fixation:	Self adhesive
Color temperature:	2700K
Color rendering index (CRI):	93 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	3,6 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	5 cm
Luminous flux (Lumen) per meter:	360 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 0,8 cm Height: 0,2 cm
Weight:	0,09 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

EUROLITE LED Strip Receiver Zone Single Color

Power supply:	12/24V DC
Power consumption:	Max. 192 W 12 V DC
	Max. 384 W 24 V DC
	96 W 12 V DC per channal
	192 W 24 V DC per channal
Output current:	Max. 2 x 8 A per channal
Power connection:	Via screw terminal
Power output:	Screw terminal
Carrier frequency:	2,4 GHz
Dimensions:	Length: 11,5 cm
	Width: 4,5 cm
	Height: 3,2 cm
Weight:	0,08 kg

EUROLITE LED Strip Remote Control Zone Single Color

Battery:	2 x 1.5 V AAA Micro LR03 alkaline manganese included
Range:	Range up to 30m
Carrier frequency:	2,4 GHz
Dimensions:	Length: 14,7 cm
	Width: 4 cm
	Height: 2,8 cm
Weight:	0,09 kg

EUROLITE Electr. LED Transformer, 12V, 4A

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	12V DC, stabilized; 4 A;
Material:	Plastic
Dimensions:	Length: 18 cm
	Width: 4 cm
	Height: 2,5 cm
Weight:	0,16 kg

IP20

EUROLITE LED Strip Power Contact 2-Pin 8mm

IP classification:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Plastic
Multicolor
Length: 16 cm
Width: 1,30 cm
Height: 0,70 cm
0,01 kg