

EUROLITE Set LED Strip RGB 5m + RF Controller + Transformer 12V

LED Strip RGB 5m, wireless remote control and Transformer 12V

Art. No.: 20000554

GTIN:



The article is no longer in our assortment.

Features:	Logistic

EUROLITE LED Strip 150 5m 5050 RGB 12V

Flexible LED strip for indoor use

- Flexible LED strip for decorative lighting
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 150 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via system controller (optional)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x illuminant, 1 x user manual

EUROLITE LED Strip RGB RF Controller

3-channel LED controller with wireless remote control for RGB LED strips 12-24V

- For controlling RGB LED strips 12-24 V
- Color selection via touch-sensitive color wheel
- RJ45 jacks for serial connection
- Dimmer electronic; program speed adjustable
- 10 integrated show programs
- Control via wireless remote control
- Operating range up to 20m

Package contents

- 1 x controller, 1 x transmitter, 1 x user manual, 1 x declaration of conformity

EUROLITE Electr. LED Transformer, 12V, 4A

Stabilized LED power supply unit DC 12 V, 4 A

- Especially for LED installations
- Input voltage AC 100-240 V

Package contents

- 1 x external mains adapter

Technical specifications:

Weight: 0,56 kg

EUROLITE LED Strip 150 5m 5050 RGB 12V

Power supply:	12V DC
Power consumption:	36 W
IP classification:	IP20
Power connection:	Fixed supply cord with open wires
Cable length:	0,15 m
LED type:	150 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	System controller (optional)
Standing/fixation:	Self adhesive
Lamps/meter:	30 pc/pcs
Power/meter:	7,2 W
Lamps/tube:	150 pc/pcs
Lamp distance:	33 mm
Cutting mark:	10 cm
Luminous flux (Lumen) per meter:	300 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 1 cm
Weight:	0,11 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Strip RGB RF Controller

Power supply:	12/24V DC
Power consumption:	Max. 360 W 12 V DC
	Max. 720 W 24 V DC
	120 W 12 V DC per channal

240 W 24 V DC per channal

Output current:	Max. 3 x 10 A per channal
Power connection:	Mains input via screw terminal
Power output:	4 x screw terminal
Battery:	Micro (AAA) (not included)
Control:	Wireless remote control
Range:	Range up to 20m
Carrier frequency:	433,920 MHz
Connections:	Signal via 2 x RJ-45 (F) mounting version
	Screw terminal
Dimensions:	Length: 9 cm
	Width: 9 cm
	Height: 2,4 cm
Weight:	0,29 kg
Remote control	
Dimensions:	Height: 2,2 cm

EUROLITE Electr. LED Transformer, 12V, 4A

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	12V DC, stabilized; 4 A;
Material:	Plastic
Dimensions:	Length: 18 cm
	Width: 4 cm
	Height: 2,5 cm
Weight:	0,16 kg