



The article is no longer in our assortment.

Features:

EUROLITE LED Strip 600 5m 3528 2700+5700K 24V

Flexible LED strip, warm white and cold white, CRI >90

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Mixed LED layout for homogeneous light distribution
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 600 powerful LEDs SMD 3528 2in1 BCL CW/WW (homogenous color mix)
- Control via Accessory
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; Clubs/dancing school; Installation; restaurants, bars and hotels
- Silent operation

EUROLITE LED Strip Receiver Zone Tunable White

Wireless receiver for controlling white LED strips 12-24 V

- Color temperature control of LED strips with warm white and cold white LEDs

EUROLITE LED Strip Remote Control Zone Tunable White

Wireless remote control for white LED strips 12-24 V

Logistic

- Controls 4 zones
- Multiple remote controls possible in one zone
- Transmission frequency 2.4 GHz
- Color temperature control of LED strips with warm white and cold white LEDs
- Brightness control
- On/off button
- Powered by a battery/battery pack
- Operating range up to 30m

EUROLITE Electr. LED Transformer, 24V, 2A

Stabilized LED power supply unit DC 24 V, 2 A

- Especially for LED installations
- Input voltage AC 100-240 V

Package contents

- 1 x external mains adapter

Technical specifications:

Weight: 440 g

EUROLITE LED Strip 600 5m 3528 2700+5700K 24V

Power supply:	24 V DC 1,7 A
Power consumption:	Max. 48 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Fixed Supply cord with open wires
LED:	600 x SMD 3528 2in1 BCL CW/WW (homogenous color mix)
Color temperature:	2700K; 5700K
Control:	Accessory
Standing/fixation:	Self adhesive
Color rendering index (CRI):	95 Ra
Lamps/meter:	120 pc/pcs
Power/meter:	9,6 W
Lamps/tube:	600 pc/pcs
Lamp distance:	8 mm
Cutting mark:	10 cm
Luminous flux (Lumen) per meter:	900 lm/m
Housing color:	White
Dimensions:	Length: 5 m Width: 1 cm Height: 2 mm
Weight:	130 g
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

EUROLITE LED Strip Receiver Zone Tunable White

Power supply:	12/24V DC
Power consumption:	Max. 192 W 12 V DC Max. 384 W 24 V DC 96 W 12 V DC per channel 192 W 24 V DC per channel
Output current:	Max. 2 x 8 A per channel
Power connection:	Via screw terminal
Carrier frequency:	2,4 GHz
Dimensions:	Length: 11,5 cm Width: 4,5 cm Height: 3,2 cm
Weight:	80 g

EUROLITE LED Strip Remote Control Zone Tunable White

Battery:	2 x 1.5 V AAA Micro LR03 alkaline manganese included
Range:	Range up to 30m
Carrier frequency:	2,4 GHz
Dimensions:	Length: 14,7 cm Width: 4 cm Height: 2,8 cm
Weight:	90 g

EUROLITE Electr. LED Transformer, 24V, 2A

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	24 V DC, stabilized; 2 A;
Material:	Plastic
Dimensions:	Length: 18 cm Width: 4 cm Height: 2,5 cm
Weight:	140 g