



The article is no longer in our assortment.

Features:

EUROLITE LED IP Strip 150 5m RGB 24V

Flexible 3in1 TCL RGB LED strip for indoor and outdoor use, 24 V

- Flexible LED strip for decorative lighting
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 150 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via system controller
- Suitable for outdoor use
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x illuminant, 1 x user manual

Logistic

EUROLITE LED Strip RGB RF Controller

3-channel LED controller with wireless remote control for RGB LED strips 12-24V

- For controlling RGB LED strips 12-24 V
- Color selection via touch-sensitive color wheel
- RJ45 jacks for serial connection
- 10 integrated show programs
- Control via wireless remote control
- Operating range up to 20m
- Dimmer electronic; program speed adjustable

Package contents

- 1 x controller, 1 x transmitter, 1 x user manual, 1 x declaration of conformity

EUROLITE LED Strip Wall Panel for RGB RF Controller

Wireless wall dimmer for RGB LED strips

- For controlling RGB LED strips 12-24 V
- Color wheel selection
- Terminals for connecting the power supply (100-240 V)
- Program speed adjustable; Dimmer electronic
- 10 integrated show programs
- Operating range up to 20m
- Flush mounting
- Finery housing (optional)

Package contents

- 1 x remote control, 1 x user manual, 1 x declaration of conformity

EUROLITE Electr. LED Transformer, 24V, 2A

Stabilized LED power supply unit DC 24 V, 2 A

- Especially for LED installations
- Input voltage AC 100-240 V

Package contents

- 1 x external mains adapter

Technical specifications:

Weight: 0,74 kg

EUROLITE LED IP Strip 150 5m RGB 24V

| | |
|----------------------------------|--|
| Power supply: | 24V DC |
| Power consumption: | 30 W |
| IP classification: | IP65 |
| Protection class: | Protection class III |
| Power connection: | Fixed supply cord with open wires |
| Cable length: | Approx. 0,15 m |
| LED type: | 150 x SMD 5050 3in1 TCL RGB (homogenous color mix) |
| Control: | System controller |
| Standing/fixation: | Self adhesive |
| Lamps/meter: | 30 pc/pcs |
| Power/meter: | 7,2 W |
| Lamps/tube: | 150 pc/pcs |
| Lamp distance: | 33 mm |
| Cutting mark: | 17 cm |
| Luminous flux (Lumen) per meter: | 300 lm/m |
| Housing color: | White |
| Dimensions: | Length: 500 cm Width: 1 cm |

| | |
|----------------------------------|---------------------------|
| | Height: 0,2 cm |
| Weight: | 0,18 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |

EUROLITE LED Strip RGB RF Controller

| | |
|--------------------|--|
| Power supply: | 12/24V DC |
| Power consumption: | Max. 360 W 12 V DC Max. 720 W 24 V DC 120 W 12 V DC per channel 240 W 24 V DC per channel |
| Output current: | Max. 3 x 10 A per channel |
| Power connection: | Mains input via screw terminal |
| Power output: | 4 x screw terminal |
| Battery: | Micro (AAA) (not included) |
| Control: | Wireless remote control |
| Range: | Range up to 20m |
| Carrier frequency: | 433,920 MHz |
| Connections: | Signal via 2 x RJ-45 (F) mounting version Screw terminal |
| Dimensions: | Length: 9 cm Width: 9 cm Height: 2,4 cm |
| Weight: | 0,29 kg |
| Remote control | |
| Dimensions: | Height: 2,2 cm |

EUROLITE LED Strip Wall Panel for RGB RF Controller

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | Max. 1 W |
| Power connection: | Mains input via screw terminal |
| Range: | Range up to 20m |
| Carrier frequency: | 433,920 MHz |
| Housing design: | Flush mounting Finery housing (optional) |
| Dimensions: | Length: 8,6 cm Width: 8,6 cm Depth: 3,4 cm |
| Weight: | 0,13 kg |

EUROLITE Electr. LED Transformer, 24V, 2A

| | |
|--------------------|------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |

| | |
|-------------------|--|
| Protection class: | Protection class II |
| Power connection: | Mains input via screw terminal |
| Power output: | Screw terminal |
| Housing color: | White matte |
| Controls: | Overload; short-circuit; overheat |
| Output: | 24 V DC, stabilized; 2 A; |
| Material: | Plastic |
| Dimensions: | Length: 18 cm Width: 4 cm Height: 2,5 cm |
| Weight: | 0,14 kg |