eurolite®

EUROLITE Set 2x LED TMH-16 Moving-Head Zoom Wash + Case

Art. No.: 20000572 GTIN:







The article is no longer in our assortment.

Features:

EUROLITE LED TMH-16 Moving Head Zoom Wash

Compact washlight with 10 W RGBW LEDs and large zoom range

- Equipped with six 10W 4in1 LEDs in the colors red, green, blue and white
- Compact lightweight
- Functions: stepless RGBW color mixture, preset colors, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Motorized zoom with 2-57° beam angle
- Positioning within 540° PAN and 190° TILT
- PAN-angle switchable between 540° and 360°
- Dimmer speed (step response) adjustable
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Control board with LCD for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 6 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- With a beam angle of 2° - 57° Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable

ROADINGER Flightcase 2x TMH FE-600

PRO flightcase for 2 x TMH FE-600

- With 2 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

23,60 kg

EUROLITE LED TMH-16 Moving Head Zoom Wash

IP classification: IP20 Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version Lamp type: LED lamp LED type: 6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) Max. TILT movement: 190° exact positioning (16 bit resolution) auto position correction (feedback) Max. PAN movement: 540°, 360° exact positioning (16 bit resolution) auto position correction (feedback) Flash rate: 0 - 18 Hz Equipment: Zoom motor driven DMX channels: 15 DMX output: 1 x 3-pin XLR (M) mounting version Cooling: Cooling fan Cooling fan Cooling fan Projection: Flicker-free Beam angle: 2° - 57°	Power supply:	100-240 V AC, 50/60 Hz
Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version Lamp type: LED lamp LED type: 6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) Max. TILT movement: 190° exact positioning (16 bit resolution) auto position correction (feedback) Max. PAN movement: 540°, 360° exact positioning (16 bit resolution) auto position correction (feedback) Flash rate: 0 - 18 Hz Equipment: Zoom motor driven DMX channels: 15 DMX output: 1 x 3-pin XLR (M) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Power consumption:	80 W
power supply cord with safety plug (provided)Power output:1 x P-Con (gray), mounting versionLamp type:LED lampLED type:6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)Max. TILT movement:190° exact positioning (16 bit resolution) auto position correction (feedback)Max. PAN movement:540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)Flash rate:0 - 18 HzEquipment:Zoom motor drivenDMX channels:15DMX input:1 x 3-pin XLR (M) mounting versionCooling:Cooling fanControl:DMX; stand-alone; sound to light via microphonePreprogrammed in:Light'J; LED PC-Control 512; Light CaptainProjection:Flicker-freeBeam angle:2° - 57°	IP classification:	IP20
Lamp type: LED lamp LED type: 6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) Max. TILT movement: 190° exact positioning (16 bit resolution) auto position correction (feedback) Max. PAN movement: 540°, 360° exact positioning (16 bit resolution) auto position correction (feedback) Max. PAN movement: 540°, 360° exact positioning (16 bit resolution) auto position correction (feedback) Flash rate: 0 - 18 Hz Equipment: Zoom motor driven DMX channels: 15 DMX input: 1 x 3-pin XLR (M) mounting version Cooling: Cooling fan Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Power connection:	
LED type:6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)Max. TILT movement:190° exact positioning (16 bit resolution) auto position correction (feedback)Max. PAN movement:540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)Max. PAN movement:0 - 18 HzEquipment:200m motor drivenDMX channels:15DMX input:1 x 3-pin XLR (M) mounting versionDMX output:1 x 3-pin XLR (F) mounting versionCooling:Cooling fanControl:DMX; stand-alone; sound to light via microphonePreprogrammed in:Light'J; LED PC-Control 512; Light CaptainProjection:Flicker-freeBeam angle:2° - 57°	Power output:	1 x P-Con (gray), mounting version
Image: Control(homogenous color mix)Max. TILT movement:190° exact positioning (16 bit resolution) auto position correction (feedback)Max. PAN movement:540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)Max. PAN movement:540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)Flash rate:0 - 18 HzEquipment:Zoom motor drivenDMX channels:15DMX input:1 x 3-pin XLR (M) mounting versionDMX output:1 x 3-pin XLR (F) mounting versionCooling:Cooling fanControl:DMX; stand-alone; sound to light via microphonePreprogrammed in:Light'J; LED PC-Control 512; Light CaptainProjection:Flicker-freeBeam angle:2° - 57°	Lamp type:	LED lamp
position correction (feedback)Max. PAN movement:540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)Flash rate:0 - 18 HzEquipment:Zoom motor drivenDMX channels:15DMX input:1 x 3-pin XLR (M) mounting versionDMX output:1 x 3-pin XLR (F) mounting versionCooling:Cooling fanControl:DMX; stand-alone; sound to light via microphonePreprogrammed in:Light'J; LED PC-Control 512; Light CaptainProjection:Flicker-freeBeam angle:2° - 57°	LED type:	
auto position correction (feedback) Flash rate: 0 - 18 Hz Equipment: Zoom motor driven DMX channels: 15 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Max. TILT movement:	, , ,
Equipment: Zoom motor driven DMX channels: 15 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Max. PAN movement:	
DMX channels: 15 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Flash rate:	0 - 18 Hz
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Equipment:	Zoom motor driven
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	DMX channels:	15
Cooling: Cooling fan Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	DMX input:	1 x 3-pin XLR (M) mounting version
Control: DMX; stand-alone; sound to light via microphone Preprogrammed in: Light´J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	DMX output:	1 x 3-pin XLR (F) mounting version
Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain Projection: Flicker-free Beam angle: 2° - 57°	Cooling:	Cooling fan
Projection: Flicker-free Beam angle: 2° - 57°	Control:	DMX; stand-alone; sound to light via microphone
Beam angle: 2° - 57°	Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
	Projection:	Flicker-free
Beam angle (1/2 peak): 2 - 31°	Beam angle:	2° - 57°
	Beam angle (1/2 peak):	2 - 31°

Beam angle (1/10 peak):	7 - 57°
Illuminance in Lux (lx):	Narrow red (R) 3m: 1071 lx, 6m: 266 lx
	Narrow green (G) 3m: 2417 lx, 6m: 608 lx
	Narrow blue (B) 3m: 523 lx, 6m: 135 lx
	Narrow cold white (CW) 3m: 3244 lx, 6m: 822 lx
	Narrow all 3m: 6846 lx, 6m: 1729 lx
	Wide red (R) 3m: 51 lx, 6m: 15 lx
	Wide green (G) 3m: 116 lx, 6m: 33 lx
	Wide blue (B) 3m: 26 lx, 6m: 8 lx
	Cold white (CW) 3m: 156 lx, 6m: 45 lx
	Wide all 3m: 328 lx, 6m: 94 lx
Housing color:	Black
Dimensions:	Width: 24,5 cm
	Depth: 19 cm
	Height: 33 cm
Weight:	5,62 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x TMH FE-600

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	24 cm x 29 cm x 30 cm
Middle compartment:	11,5 cm x 29 cm x 30 cm
Inside dimensions:	67 cm x 29 cm x 30 cm
Dimensions:	Width: 71,5 cm
	Depth: 33 cm
	Height: 33 cm
Weight:	10,40 kg