

EUROLITE Set 2x LED CBB-4 COB RGB Bar + Case

2x LED light effect bar with RGB color mixing and IR remote control incl. PRO flightcase

Art. No.: 2000574

GTIN:



Features:

- 4 LEDs 23 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 39°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; stage; clubs/dancing school; decoration; mobile djs / entertainer; video and photography
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 2x LED CBB-4
- <h2 class="featureSatz">PRO flightcase for 2 x Eurolite LED CBB-4</h2>
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

Technical specifications:

Weight: 15.19 kg

EUROLITE LED CBB-4 COB RGB Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 23 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix)
Flash rate:	0.3 - 23 Hz
DMX channels:	3; 5; 12; 15; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	39°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 46 cm Depth: 16 cm Height: 16 cm
Weight:	3.97 kg
Noise classification:	Class 2 (slight noise)
Diameter mounting holes:	3 x Ø11mm; 4 x Ø8mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.1 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED CBB-4

Use of brands:	Branded hardware
Device compartment:	46.5 cm x 11 cm x 17 cm
Middle compartment:	48 cm x 8.5 cm x 17 cm
Inside dimensions:	48 cm x 30.5 cm x 17 cm
Weight:	7.25 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual