

## EUROLITE Set 8x LED PAR-64 COB 3000K 100W Zoom bk + Case

8x PAR spot with warm white 100 W COB LED and manual zoom incl. Flightcase with wheels

Art. No.: 2000578

GTIN:



### Features:

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Dimmer speed (step response) adjustable; Gamma correction adjustable; pulse-width modulation variable
- Strobe effect
- The device is cooled by cooling fan
- Control via DMX
- Fixtures available for Light´J; Light Captain; Colorchief
- Flicker-free
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; video and photography
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 8x PAR-64/ML-56</p>
- <h2 class="featureSatz">Trunk case with castors</h2>With 8 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with felt cover
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

### Logistic

- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 82.40 kg

---

### EUROLITE LED PAR-64 COB 3000K 100W Zoom bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 25 Hz
DMX channels:	1; 2; 3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Color temperature:	3000K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 3m: 15535 lx, 6m: 3666 lx Wide warm white (WW) 3m: 2387 lx, 6m: 654 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Width: 26 cm Depth: 43.5 cm Height: 37.5 cm
Weight:	3.55 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1.5 m

Shape:	Octagonal
Material:	Aluminum, 0.5 mm
Dimensions:	Width: 24.8 cm Height: 24.8 cm Diameter: Ø 19.8 cm
Cable length:	Approx. 1.8 m
Color:	Black
Diameter mounting holes:	1 x Ø10mm; 2 x Ø8mm
Material:	Aluminum, 4 mm

### **ROADINGER Flightcase 8x PAR-64/ML-56**

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	24 cm x 24.5 cm x 42 cm
Inside dimensions:	96 cm x 49 cm x 42 cm
Dimensions:	Width: 109 cm Depth: 57.5 cm Height: 68.5 cm
Weight:	41.70 kg

### **Scope of delivery:**

- 1 x spotlight
- 1 x power cord
- 1 x filter frame
- 1 x XLR cable
- 1 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x user manual