

EUROLITE Set 4x LED IP PAR 14x8W QCL + Case

4x weather-proof spotlight with RGBW color mixing, frost filters and PRO flightcase with wheels

Art. No.: 2000581

GTIN:



Features:

- 14 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels
- <h2 class="featureSatz">Trunk case with castors, PRO version</h2>For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks

Logistic

- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 53.10 kg

EUROLITE LED IP PAR 14x8W QCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle (1/2 peak):	15° 27° 30° 60°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome LCD display
Color:	Black
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm

Weight:	7.15 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	27 cm x 27 cm x 28 cm
Accessory compartment:	10 cm x 56 cm x 28 cm
Inside dimensions:	65 cm x 55 cm x 30.5 cm
Dimensions:	Length: 71 cm Width: 60 cm Height: 53 cm
Weight:	20.20 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 3 x frost filter
 1 x XLR cable
 2 x knurled screw