

EUROLITE Set 4x AKKU IP UP-4 Plus HCL Spot WDMX + Case with charging function

4x IP65 uplight with replaceable battery incl. PRO flightcase with charging function for 8 batteries

GTIN:



List price: 3033.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX

IP65 uplight with replaceable battery, RGBWA+UV LEDs, WDMX and IR remote control

- Quick and tool-free battery change, additional rechargeable battery optionally available
- Integrated W-DMX transceiver for wireless DMX Control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Battery operation up to 9,5h depending on program used
- 4 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 49 integrated show programs
- Direct color selection for 63 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; W-DMX by wireless solution; Master/slave function; Sound to light via Microphone; IR remote control
- With a beam angle of 16°
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; Rental
- Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Cordless, flexible and versatile

Logistic

- Rubber feet
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x power cord, 1 x external mains adapter, 1 x remote control, 1 x diffuser cover, 2 x screw, 1 x plate, 1 x user manual, 1 x declaration of conformity, 1 x battery, 1 x battery pack

ROADINGER Flightcase 4x AKKU IP UP-4 Plus HCL Spot WDMX with Charging Function

Trunk case with castors

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

Package contents

- 1 x case, 1 x power cord, 1 x user manual

Technical specifications:

Weight:	39,80 kg
---------	----------

EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 3 A
Pin configuration:	Inside + / outside -
Power consumption:	35 W
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Battery/battery pack
Battery pack type:	1 x lithium ion 11,1 V, 13000 mAh, 144,3 Wh
Battery pack:	Battery operation up to 9,5h depending on program used Recharging time 8h
Lamp type:	LED lamp
LED:	4 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	6; 8; 12
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; W-DMX by wireless solution; Master/slave function; Sound to light via Microphone; IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3

Beam angle:	16°
Beam angle (1/2 peak):	16°
Housing color:	Black
Attachment system:	Bracket for floor use
Carrier frequency:	2,4 GHz
Transport aid:	Rubber feet
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 17,1 cm Depth: 13,8 cm Height: 20 cm
Weight:	4,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU IP UP-4 Plus HCL Spot WDMX with Charging Function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, F 5 A Fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Birch multiplex
Color:	Black, laminated
Accessory compartment:	37 cm x 8 cm x 19,5 cm
Compartment dimensions:	17,8 cm x 15,4 cm x 19,5 cm
Dimensions:	Width: 68 cm Depth: 46 cm Height: 38 cm
Weight:	20,20 kg