

EUROLITE Set 2x LED STP-10 ABL Sunbar + Case

2x sunbar with ambient light including PRO flightcase

Art. No.: 20000602

GTIN:





The article is no longer in our assortment.

Features: Logistic

EUROLITE LED STP-10 ABL Sunbar

Sunbar with ambient light

- The white LEDs have a narrow beam angle and produce clearly defined beams
- Creates a unique ambience
- 60 powerful LEDs 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix)
 LEDs controlled separately
- 10 powerful LEDs 3 W high-power warm white (WW)
 LEDs controlled separately
- Mood lights; color animations
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; Art-Net
- With mounting bracket
- Silent operation
- Strobe effect
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; restaurants, bars and hotels
- Application possibility: Suspended; wall mounting

ROADINGER Flightcase 2x LED STP-10 ABL Sunbar

Carrying case, PRO version

- With accessory compartment
- With 2 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 16,00 kg

EUROLITE LED STP-10 ABL Sunbar

P classification: IP20	Power supply:	100-240 V AC, 50/60 Hz
Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x P-Con (gray), mounting version LED lamp LED type: 60 x 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix) 10 x 3 W high-power warm white (WW) Flash rate: 0 - 18 Hz DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	Power consumption:	70 W
power supply cord with safety plug (provided) Power output: LED lamp LED type: 60 x 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix) 10 x 3 W high-power warm white (WW) Flash rate: 0 - 18 Hz DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	IP classification:	IP20
LED lamp LED type: 60 x 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix) 10 x 3 W high-power warm white (WW) Flash rate: 0 - 18 Hz DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Power connection:	
LED type: 60 x 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix) 10 x 3 W high-power warm white (WW) Flash rate: 0 - 18 Hz DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Power output:	1 x P-Con (gray), mounting version
(homogenous color mix) 10 x 3 W high-power warm white (WW) Flash rate: 0 - 18 Hz DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Lamp type:	LED lamp
Flash rate: DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	LED type:	(homogenous color mix)
DMX channels: 11; 20; 47; 190 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Flash rate:	
DMX output: 1 x 3-pin XLR (M) mounting version 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX channels:	
Network connection: Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX input:	. , , ,
mounting version Cooling: Passive convection cooling Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX output:	
Control: Stand-alone; DMX; sound to light via microphone; Art-Net Housing color: Black Attachment system: Mounting bracket Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Network connection:	` ,
Art-Net Housing color: Black Attachment system: Mounting bracket Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Cooling:	Passive convection cooling
Attachment system: Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Control:	· · · · · · · · · · · · · · · · · · ·
Dimensions: Length: 78 cm Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Depth: 14 cm Height: 10,5 cm Weight: 3,50 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Attachment system:	Mounting bracket
Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 14 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	3,50 kg
Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED STP-10 ABL Sunbar

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Plywood multi-layer glued, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Accessory compartment:	78 cm x 10 cm x 13 cm
Device compartment:	78 cm x 7 cm x 13 cm
Inside dimensions:	78 cm x 35 cm x 13 cm
Dimensions:	Width: 84 cm
	Depth: 23 cm
	Height: 41 cm
Weight:	9,00 kg