

## EUROLITE Set 2x LED TMH-X Bar 5 Beam + Case

2x narrow angle LED Moving Bar with 5 RGBW LEDs including PRO flightcase with wheels

Art. No.: 2000605

GTIN:



### Features:

- Moving Beam bar equipped with five 15 W COB LEDs with RGBW colors
- Each LED can be controlled individually
- Narrow beam angle
- With Infinity function for unlimited TILT movement
- Positioning within 540° PAN and 360° TILT
- Automatic position correction for PAN
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Colored beams in red, green, blue and white
- Stepless RGBW color mixture
- Color presets
- Strobe effect with variable speed
- Internal programs
- Exact positioning via 16 bit PAN/TILT movement resolution
- Dimmer
- Control board with LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 5 LEDs 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 3°

### Logistic

- Multicolor LCD display
- <p>ROADINGER Flightcase 2x LED TMH-X Bar 5
- <h2 class="featureSatz">PRO flightcase for 2 x Eurolite LED TMH-X Bar 5</h2>High-quality workmanship with birch multiplex , dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 41.00 kg

---

### EUROLITE LED TMH-X Bar 5 Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	5 x 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Max. TILT movement:	360° exact positioning (16 bit resolution) plus infinity
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	16; 32
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 1646 lx, 6m: 532 lx Green (G) 3m: 4112 lx, 6m: 1249 lx Blue (B) 3m: 1120 lx, 6m: 345 lx Cold white (CW) 3m: 6739 lx, 6m: 2089 lx All 3m: 10763 lx, 6m: 3175 lx
Housing color:	Black
Display type:	Multicolor LCD display

Dimensions:	Width: 43 cm Depth: 19.5 cm Height: 30 cm
Weight:	8.90 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x LED TMH-X Bar 5**

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex
Color:	Dark brown, laminated
Inside dimensions:	60 cm x 48 cm x 37 cm
Device compartment:	10.5 cm x 43.5 cm x 35.5 cm
Accessory compartment:	11 cm x 47.5 cm x 37 cm
Dimensions:	Width: 64 cm Depth: 52 cm Height: 54 cm
Weight:	22.90 kg

#### **Scope of delivery:**

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket