eurolite®

EUROLITE Set 2x LED TMH-X19 + Case

Art. No.: 20000614 GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED TMH-X19 Moving-Head Wash Zoom

Washlight with 19 x 25 W LEDs, 7in1 SCL RGBWAL/UV-Farbmischung and motorized zoom

- Moving Head Washlight with nineteen 7in1 LEDs and zoom
- Equipped with nineteen 25 W LEDs in the colors red, green, blue, amber, white, lemon and UV
- 22 or 36 DMX channels selectable
- Different LED segments, which can be controlled individually via DMX
- Positioning within 540° PAN and 270° TILT
- Stepless RGBAWL+UV color mixture
- Color presets
- 12 Macros
- 5 internal color-programs
- Dimmer
- Dimmer speed (step response) adjustable
- Motorized zoom with 4-58° beam angle
- Sound-control via built-in microphone; sensitivity adjustable
- Strobe effect with adjustable speed, random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 360°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with color LCD for adjusting the DMX-starting address, PAN/TILT Reverse, Reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 19 powerful LEDs 25 W high-power 7in1 SCL RGBWAL/UV (homogenous color mix)
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Exact positioning (16 bit resolution)

- Zoom motor driven
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 4° 58°
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x XLR cable

ROADINGER Flightcase 2x LED TMH-X19 Moving head

Trunk case with castors, PRO version

- High-quality workmanship with plywood multi-layer glued , black, laminated
- Castors
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

57,70 kg

EUROLITE LED TMH-X19 Moving-Head Wash Zoom

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	19 x 25 W high-power 7in1 SCL RGBWAL/UV (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	22; 36
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free

Beam angle:	4° - 58°
Beam angle (1/2 peak):	4 - 31°
Beam angle (1/10 peak):	9 - 58°
Housing color:	Black
Dimensions:	Width: 38 cm
	Depth: 23,1 cm
	Height: 49,8 cm
Weight:	14,40 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED TMH-X19 Moving head

Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Plywood multi-layer glued
Color:	Black, laminated
Middle compartment:	11,5 cm x 55 cm x 36 cm
Device compartment:	29 cm x 55 cm x 36 cm
Inside dimensions:	55 cm x 36 cm
Weight:	25,10 kg