

EUROLITE Set 4x LED STP-10 Sunbar 3200K 10x5W Light Bar + Case

Art. No.: 20000616

4x LED light bar with warm white beam effects including PRO flightcase

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED STP-10 Sunbar 3200K 10x5W Light Bar 6°

LED light bar with warm white beam effects and narrow beam angle

- 10 powerful LEDs 5 W high-power warm white (WW)
 LEDs controlled separately
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; master/slave function; stand-alone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 6°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; installation; stage; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual, 1 x plug (male)

Logistic

ROADINGER Flightcase 4x LED STP-7

Trunk case

- ,
- Branded hardware
- Made in Europe

- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 35,75 kg |
|---------|----------|

EUROLITE LED STP-10 Sunbar 3200K 10x5W Light Bar 6°

| | |
|------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 60 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 10 x 5 W high-power warm white (WW) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 1; 3; 5; 10; 15 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; sound to light via microphone; master/slave function; stand-alone |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Beam angle: | 6° |
| Beam angle (1/2 peak): | 6° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 99,5 cm Depth: 15 cm Height: 80 cm |
| Weight: | 3,90 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED STP-7

| | |
|---------------------|--------------------------|
| Use of brands: | Branded hardware |
| Inside dimensions: | 100 cm x 37,5 cm x 15 cm |
| Device compartment: | 100 cm x 7,5 cm x 15 cm |
| Weight: | 16,00 kg |