

# OMNITRONIC Set MOM-10BT4 Receiver module + Bodypack transmitter + Landerschaften (micropho

GTIN:



## The article is no longer in our assortment.

Features: Logistic

#### **OMNITRONIC MOM-10BT4 Receiver Module**

Receiver module for UHF frequencies (microphone, bodypack + audio link module)

- For retrofitting the MOM-10BT4 modular PA system
- Up to 4 receiving modules can be retrofitted
- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- LEDs for power, carrier and audio signals
- UHF 823 832 MHz License-free and approved in large parts of Europe
- UHF 863 865 MHz License-free and approved in Europe
- Operating range up to 30m with line-of-sight

#### Package contents

- 1 x receiver, 1 x user manual, 1 x declaration of conformity

#### **OMNITRONIC MOM-10BT4 Bodypack Transmitter**

Bodypack transmitter with 16 UHF frequencies (823-832 & 863-865 MHz)

- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- Sensitivity adjustable
- LED indicator for battery capacity
- Belt clip
- Headset microphone and lavalier microphone available as accessories
- Operating range up to 30m with line-of-sight
- UHF 823 832 MHz License-free and approved in large parts of Europe
- UHF 863 865 MHz License-free and approved in Europe
- LCD display
- Charge status indicator

#### Package contents

- 1 x transmitter, 1 x user manual, 1 x declaration of conformity

### **OMNITRONIC MOM-10BT4 Lavalier Microphone**

Black, inconspicuous tie-clip microphone

- For attaching to the user's tie, shirt or collar
- Low weight
- Polar pattern: Cardioid
- For application areas such as: Theater; product presentations and lectures

### Package contents

- 1 x microphone

## **Technical specifications:**

Weight: 0,21 kg

### **OMNITRONIC MOM-10BT4 Receiver Module**

Type:	Receiver
Power supply:	12V DC 150 mA
Frequency range:	50 - 15000 Hz
S/N ratio:	>80 dB
THD:	<0,1 % at 1 kHz
Sensitivity:	-95 dB
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0,01 %
Frequency selection:	16 switchable frequencies
Control elements:	Frequency selector switch, level control
Dimensions:	Width: 7,1 cm
	Depth: 13,9 cm
	Height: 3 cm
Weight:	0,09 kg

### **OMNITRONIC MOM-10BT4 Bodypack Transmitter**

Type:	Pocket transmitter
Power supply:	3V DC
Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0,01 %
RF power output:	10 mW
Frequency selection:	16 switchable frequencies

Connector type:	Mini XLR (M) 3-pin mounting version
Display type:	LCD display
Display:	Channel , charge status indicator
Switch:	On/off switch
Material:	Plastic
Dimensions:	Width: 6,6 cm
	Depth: 2,2 cm
	Height: 10,8 cm
Weight:	0,10 kg

## **OMNITRONIC MOM-10BT4 Lavalier Microphone**

Type:	Lavalier microphone
Power supply:	1,5-10V DC
Power connection:	Mains input via Mini XLR (F) 3-pin
Cable length:	1 m
Capsule type:	Condenser
Polar pattern:	Cardioid
Frequency range:	50 - 20000 Hz
Sensitivity:	-37 dB
Max. SPL:	120 dB
Material:	Metal
Color:	Black
Weight:	0,02 kg