

## EUROLITE Set 6x AKKU TL-3 TCL Trusslight QuickDMX + Case TDV-1

6x Trusslight with 3 x 3 W 3in1 LED including universal case

Art. No.: 20000625

GTIN: 4026397663518



### Features:

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- 3 LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 11°
- LCD display
- 3 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- <p>ROADINGER TDV-1 Universal Case Pick
- <h2 class="featureSatz">Universal case with flexible foam dividers</h2>With dividers

### Logistic

EAN / GTIN: 4026397663518

Weight: 13,00 kg

Length: 0.82 m

Width: 0.41 m

Heigh: 0.52 m

- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 11.07 kg |
|---------|----------|

### EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

|                         |                                                                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                |
| Power consumption:      | 25 W                                                                                                                                                                  |
| IP classification:      | IP20                                                                                                                                                                  |
| Protection class:       | Protection class I                                                                                                                                                    |
| Power connection:       | Battery/battery pack<br>Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                              |
| Cable length:           | Approx. 1.2 m                                                                                                                                                         |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                                                                |
| Fuse:                   | 5 x 20 mm, F 5 A                                                                                                                                                      |
| Battery pack type:      | 1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh                                                                                                                            |
| Battery pack:           | Battery operation up to 16h depending on program used<br>Recharging time 3h                                                                                           |
| Lamp type:              | LED lamp                                                                                                                                                              |
| LED type:               | 3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)                                                                                                                  |
| Flash rate:             | 0 - 23 Hz                                                                                                                                                             |
| DMX channels:           | 3; 5; 8                                                                                                                                                               |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                                                    |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                                                    |
| Cooling:                | Passive convection cooling                                                                                                                                            |
| Control:                | DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone                                                                                          |
| Fixtures available for: | Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free                                                                                                                                                          |
| Carrier frequency:      | 2.4 GHz                                                                                                                                                               |
| Beam angle:             | 11°                                                                                                                                                                   |
| Beam angle (1/2 peak):  | 11°                                                                                                                                                                   |

|                         |                                                         |
|-------------------------|---------------------------------------------------------|
| Beam angle (1/10 peak): | 24°                                                     |
| Housing color:          | Black                                                   |
| Attachment system:      | M10 thread                                              |
| Display type:           | LCD display                                             |
| Transport aid:          | 3 x rubber feet                                         |
| Dimensions:             | Width: 12.1 cm<br>Depth: 10.8 cm<br>Height: 14.5 cm     |
| Weight:                 | 1.27 kg                                                 |
| Noise classification:   | Class 0 (no noise at all)                               |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product:        | Not designed for household room illumination            |
| Intended use:           | Show effect lighting                                    |

#### **ROADINGER TDV-1 Universal Case Pick**

|                          |                                               |
|--------------------------|-----------------------------------------------|
| Maximum load:            | 25 kg                                         |
| Aluminum profile frames: | 12 mm                                         |
| Carrying handle:         | 1 pc/pcs                                      |
| Stop hinge:              | 3 pc/pcs                                      |
| Lock:                    | Spring lock: 2 pc/pcs with shut-off function  |
| Material:                | Plastic, 3 mm                                 |
| Color:                   | Black, imprinted                              |
| Inside dimensions:       | 52 cm x 28.5 cm x 20 cm                       |
| Dimensions:              | Width: 54 cm<br>Depth: 31 cm<br>Height: 26 cm |
| Weight:                  | 3.45 kg                                       |

#### **Scope of delivery:**

##### **6 x EUROLITE AKKU TL-3 TCL Trusslight QuickDMX**

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x remote control  
 1 x battery  
 1 x declaration of conformity

##### **1 x ROADINGER TDV-1 Universal Case Pick**

1 x case