

## EUROLITE Set 4x LED SLS-603 TCL UV Floor + Case TDV-1

4x flat spotlight with 5 x 3 W 3in1 LED and one 3 W UV LED including case

Art. No.: 2000633

GTIN:



**List price: 446.25 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED SLS-603 TCL + UV Floor

Flat spotlight with 5 x 3 W 3in1 LED (RGB) and one 3 W UV LED, incl. IR remote control

- Slim design for space-saving applications
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Flat, lightweight ABS housing with rubber feet
- Sits flat on the floor or inside a truss
- DMX and power terminals intelligently designed for easy wiring
- Mains input and output for power linking up to 8 units
- 6 powerful LEDs 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Integrated Showprograms
- Can be operated in 4; 8 CH mode
- The device is cooled by cooling fan
- Controlling by stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain
- Effect: UV effect; Strobe effect
- With a beam angle of 11°
- With double bracket

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

#### ROADINGER Universal Case Pick TDV-1

Universal case with flexible foam dividers

### Logistic

- Individual separation of the interior via flexible foam dividers
- With Dividers
- High-quality workmanship with birch multiplex 3 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- 1 rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x case

### Technical specifications:

---

Weight: 9,11 kg

---

#### EUROLITE LED SLS-603 TCL + UV Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	6 x 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
DMX channels:	4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	28°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
Weight:	1,41 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in

#### Legal specifications

---

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

**ROADINGER Universal Case Pick TDV-1**

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Birch multiplex, 3 mm
Color:	Black, laminated
Inside dimensions:	52 cm x 28,5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3,45 kg