eurolite®

EUROLITE Set 2x LED IP PAR 14x10W HCL + Case with wheels

2x weather-proof spotlight with RGBAW+UV color mixing and frost filters incl. PRO flightcase

Art. No.: 20000656 GTIN: 4026397670936







The article is no longer in our assortment.

Features:

EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 HCL RGBWA/UV color mixing and frost filters

- 14 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand
- Package contents
- 1 x spotlight, 1 x power cord, 1 x remote control, 3 x frost filter, 1 x XLR cable, 2 x knurled screw, 1 x user manual

Logistic

EAN / GTIN: 4026397670936 Weight: 31,00 kg Length: 0.60 m Width: 0.80 m Heigth: 1.00 m Bulky product

ROADINGER Flightcase 2x TMH-30/40/60 with wheels

PRO flightcase with castors for 2 x TMH-30/TMH-40/TMH-60

- Developed for 51785980 EUROLITE LED TMH-30 Moving-Head Spot COB, 51785996 EUROLITE LED TMH-40 Moving-Head Wash, 51785984 EUROLITE LED TMH-60 Moving-Head Spot COB or comparable Moving Heads
- Suitable for 2 units
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 2 chrome case handles
- For perfect protection
- Castors
- Branded hardware
- Made in Europe

Technical specifications:

Weight:

29,60 kg

EUROLITE LED IP PAR 14x10W HCL

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|--|
| Power consumption: | 95 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 14 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Frost filter |
| DMX channels: | 3; 5; 6; 8; 12 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control |
| Preprogrammed in: | Light'J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 15° |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Beam angle (1/2 peak): | 15° 27° 30° 60° |
|--------------------------|---|
| Housing color: | Black matte |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Material: | Aluminum casting |
| Dimensions: | Width: 31 cm Depth: 22,5 cm Height: 36,5 cm |
| Weight: | 6,80 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Mounting bracket | |
| Diameter mounting holes: | 3 x Ø11mm |
| Material: | Metal, 3 mm |
| Power cord | |
| Cable construction: | 3 x 1,0 mm² H05RN-F |
| Cable length: | Approx. 1,2 m |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Frost filter | |
| Material: | Plastic, 2 mm |
| Dimensions: | Diameter: Ø 20,5 cm |
| XLR cable | |
| Cable length: | Approx. 1,5 m |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x TMH-30/40/60 with wheels

| 50 kg |
|-------------------------|
| Castors |
| Branded hardware |
| Birch multiplex, 7 mm |
| Dark brown, laminated |
| 25,5 cm x 31 cm x 31 cm |
| 11,5 cm x 31 cm x 31 cm |
| 67 cm x 31 cm x 31 cm |
| Width: 71 cm |
| Depth: 35 cm |
| Height: 53 cm |
| 16,00 kg |
| |