

## EUROLITE Set 4x LED BAR-12 QCL RGB+UV Bar + Case

4x light effect bar (1 m) with RGB+UV color mixing including flightcase

Art. No.: 2000664

GTIN: 4026397671032



### Features:

- 12 LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect; UV effect
  - Integrated show programs
  - Direct color selection for 20 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Fixtures available for LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 3; Colorchief
  - Flicker-free
  - With a beam angle of 20°
  - With mounting bracket
  - 4 digit 7-segment LED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
  - Silent operation
  - Application possibility: Suspended; wall mounting
- screw**
- M8 thread
  - ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB
  - ## Carrying case

High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
  - Interior with foam padding

### Logistic

EAN / GTIN: 4026397671032

Weight: 26,50 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 22.30 kg

---

### EUROLITE LED BAR-12 QCL RGB+UV Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Wavelength:	Ultra violet (UV) 399 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Length: 100 cm Depth: 6.5 cm

	Height: 10.3 cm
Weight:	2.85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Cable length:	1.2 m
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 2 x Ø7mm
Material:	Metal, 2 mm
Thread:	M8 thread x 16 mm
Material:	Rubber
Dimensions:	Height: 0.3 cm Diameter: Ø 2 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB**

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	108 cm x 44 cm x 7.5 cm
Device compartment:	108 cm x 6.5 cm x 7.5 cm
Dimensions:	Width: 117 cm Depth: 48 cm Height: 17 cm
Weight:	10.90 kg

#### **Scope of delivery:**

1 x bar  
 1 x power cord  
 2 x mounting bracket  
 2 x screw  
 2 x washer  
 1 x user manual