

EUROLITE AKKU Mobile Bundle

4 battery-powered spotlights incl. soft bag, DMX controller incl. flightcase and wireless DMX system

Art. No.: 2000668

GTIN: 4026397606607



Features:

- Cordless, flexible and versatile
- Battery operation up to 12h depending on program used
- Integrated automatic charging of the battery and status indicator
- 6 LEDs 4 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- Fixtures available for Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 18°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>EUROLITE QuickDMX USB Wireless Transmitter/Receiver
- <h2 class="featureSatz">Wireless miniature DMX transceiver 2.4 GHz, phantom powered</h2>User-friendly USB plug with swivel antenna

Logistic

EAN / GTIN: 4026397606607

Weight: 20,50 kg

Length: 0.60 m

Width: 0.80 m

Height: 1.00 m

Bulky product

- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference
- <p>EUROLITE QuickDMX Wireless Transmitter/Receiver
- <h2 class="featureSatz">Wireless DMX system 2.4 GHz</h2>Auto-switching transceiver
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference
- <p>EUROLITE SB-4 Soft Bag L
- <h2 class="featureSatz">Black soft bag for up to 4 devices, 320 x 320 x 200 mm</h2>Practical transport bag offers enough space for several lighting effects and accessories
- With dividers
- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps
- <p>EUROLITE DMX LED Color Chief Controller
- <h2 class="featureSatz">DMX lighting desk with innovative control concept for LED spotlights</h2>Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- <p>ROADINGER Mixer Case Pro MCA-19, black, 4U
- <h2 class="featureSatz">Rack case</h2>Upward tilted profile rails for top-operated units
- 4 U
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle

- 2 high-quality butterfly locks with shut-off function
- Rubber feet
- With profile rails suitable for 19" units
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18.69 kg

EUROLITE AKKU PAR 6 QCL

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14.8 V, 4400 mAh, 65.12 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3.5h
Lamp type:	LED lamp
LED type:	6 x 4 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1.5 - 50 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Fixtures available for:	Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	23400 Hz
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	36°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display

Dimensions:	Width: 17.7 cm Depth: 14.3 cm Height: 21.1 cm
Weight:	2.52 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 1.5 mm
Cable length:	Approx. 2 m
Color:	Black
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

EUROLITE QuickDMX Wireless Transmitter/Receiver

Power supply:	100-240 V AC, 50/60 Hz 5V DC 500 mA
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Input 512 Output 512
DMX input:	1 x 3-pin XLR (M) mounting version

DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 21.2 cm Depth: 10 cm Height: 7.5 cm
Weight:	0.29 kg

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0.52 kg

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated

Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

ROADINGER Mixer Case Pro MCA-19, black, 4U

Maximum load:	25 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	44.6 cm x 23.8 cm x 10.5 cm
Front panel width:	19"
Mounting height:	Approx. 18 cm (4 U)
Mounting depth:	105 mm
Housing design:	4 U
Dimensions:	Width: 54 cm Depth: 27 cm Height: 23.5 cm
Weight:	5.50 kg

Scope of delivery:

4 x EUROLITE AKKU PAR 6 QCL

- 1 x spotlight
- 1 x power cord
- 1 x XLR cable
- 1 x remote control
- 1 x battery
- 1 x user manual

4 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

- 1 x device
- 1 x user manual
- 1 x declaration of conformity

1 x EUROLITE QuickDMX Wireless Transmitter/Receiver

- 1 x device
- 1 x user manual
- 1 x external mains adapter
- 1 x USB cable
- 1 x antenna
- 1 x declaration of conformity

1 x EUROLITE SB-4 Soft Bag L

1 x bag

1 x EUROLITE DMX LED Color Chief Controller

1 x controller

1 x user manual

1 x external mains adapter