

## EUROLITE Set LED IP PAR 7x9W SCL Spot + 2x Diffuser cover (15x60° and 40°): 20000672

Weatherproof spotlight with 7 SCL LEDs and RGBA/CW/WW+UV color mixing incl. 2x diffuser cover

GTIN: 4026397362336



**List price: 403.41 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 7x9W SCL spot

Weather-proof (IP65) spotlight with 7 x 7in1 LED and RGBA/CW/WW+UV color mixing

- Stepless color blend, color change, color fade, dimmer and strobe effect
- Mains input and output for power linking up to 8 units
- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- Can be operated in 3; 5; 7; 9; 13 CH mode
- The device is cooled by passive convection cooling
- Controlling by DMX; stand-alone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display for easy controlling
- Suitable for outdoor use

#### Package contents

- 1 x remote control, 1 x device, 1 x user manual, 1 x power cord, 1 x battery

### Logistic

EAN / GTIN: 4026397362336

Weight: 5,20 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

#### EUROLITE Diffuser Cover 15x60° for IP PAR-7<p class='attributgroup'>Package contents

- 1 x diffuser cover

#### EUROLITE Diffuser Cover 40° for IP PAR-7<p class='attributgroup'>Package contents

- 1 x diffusor cover

## Technical specifications:

---

Weight: 4,27 kg

---

### EUROLITE LED IP PAR 7x9W SCL spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; Light 'J'; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Dimensions:	Width: 25,5 cm Depth: 15,3 cm Height: 28,1 cm
Weight:	4,07 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE Diffuser Cover 15x60° for IP PAR-7

Dimensions: Diameter: Ø 18,50 cm

---

Weight: 100 g

---

**EUROLITE Diffuser Cover 40° for IP PAR-7**

Dimensions: Diameter: Ø 18,50 cm

---

Weight: 100 g

---