

EUROLITE Set 4x Multiflood Pro IP RGBW Wash/Frost + Case

4x bright LED outdoor spot with wireless DMX receiver incl. PRO flightcase

Art. No.: 2000677

GTIN: 4026397360929



The article is no longer in our assortment.

Features:

EUROLITE Multiflood Pro IP RGBW Wash/Frost

Bright LED outdoor spot with wireless DMX receiver

- Washlight and strobe
- Suitable for external use (IP65)
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- 36 high-power 15 W RGBW LEDs (4in1)
- 16° standard beam angle
- 2 frost filters (25° and 45°) for a softer light with larger beam angles, included in delivery
- Flicker-free projection
- Direct color selection for 20 preset colors
- Stepless RGBW color blend
- Dimmer speed (step response) adjustable
- Addressing and setting via control panel with LED screen and four operating buttons
- Swivel mounting bracket with locking possibility
- Hanging installation via quick-lock Omega holders
- Additional rubber feet protect the device when positioned on the ground
- IP T-Con terminals for power linking up to 8 units
- 36 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by cooling fan
- Control via W-DMX by wireless solution; Sound to light via Microphone; Master/slave function; DMX; stand-alone
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 16°
- Suitable for outdoor use IP65

Package contents

Logistic

EAN / GTIN: 4026397360929

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x xLR cable, 1 x omega bracket, 2 x diffusor cover, 1 x plug (male)

ROADINGER Flightcase 4x Multiflood Pro

Trunk case with castors, PRO version

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware

Technical specifications:

Weight: 68,55 kg

EUROLITE Multiflood Pro IP RGBW Wash/Frost

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	215 W
IP classification:	IP65
Protection class:	Protection class I
Lamp type:	LED lamp
LED:	36 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Cooling fan
Control:	W-DMX by wireless solution; Sound to light via Microphone; Master/slave function; DMX; stand- alone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Carrier frequency:	2,4 GHz
Beam angle:	16°
Beam angle (1/2 peak):	16° 25° 45°
Beam angle (1/10 peak):	35°
Housing color:	Black
Dimensions:	Length: 16 cm Width: 49 cm

	Height: 32 cm
Weight:	12,05 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Multiflood Pro

Maximum load:	60 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	16 cm x 32,5 cm x 51 cm
Middle compartment:	10 cm x 34 cm x 51 cm
Inside dimensions:	74 cm x 34 cm x 51 cm
Dimensions:	Length: 89 cm Width: 38 cm Height: 72,5 cm
Weight:	20,35 kg